

FIPDes

Food Innovation & Product Design

FIPDes Day 2025 International talents in Food Innovation and Product Design

Students' Book of Executive Summaries



Congratulations to the FIPDes Cohort 12!



Table of contents

Introduction Barbara Rega	7
Juan Pablo ADAME PATIÑO Comparatively Exploring the Effect of Yeast on Oven Spring Using Conventional and Ohmic Baking	8
Muskan AGARWAL Performance Evaluation of Sugar Alternatives in No Added Sugar Muffins	14
Jenipher ALUM Optimisation of the Technological and Organoleptic quality of lean bread enriched with seeds and grains	15
Blandine BOUCHELET DE VENDEGIES Towards the use of sustainable alternative caseins: optimization of the stretching properties of cheese analogues hybrid matrices	16
Constanza Eleonor CABALLERO GÜERECA Physicochemical Evaluation of Crackers Enriched With Mealworm (T. molitor) Meal: Influence of Nutrient Composition and Storage	17
Elizabeth CODJOE Towards a Circular Future: A Roadmap for Sustainable Industrial Packaging	68
Charlotte DELATTRE Thermal Processing Effects on Pulse Matrix: A Multiscale Approach	21

Table of contents

Oğuzhan DURSUN Impact and Lifecycle of New Barrier Polymer in Beverage Carton Recycling - A Lab-Scale Experimental Study	22
Julio Alberto GARCIA DOMINGUEZ Quantification of Yeast Metabolites in Dough	26
Ana Maria HENAO TOBON Mono Material Lid Film Selection for Ready Meals	27
Rinë KRASNIQI Exploring the capacity of a novel enzyme preparation to reduce the gluten allergenicity of foods during digestion	31
Anum MAHMOOD Aseptic Packaging for Energy Efficiency and Resilient Food Supply: A Comparative Study of Milk Preservation	36
Ann MATHEW Understanding Oral Meltability of Chocolate: A Sensory and Instrumental Approach	41
Phuong Linh NGUYEN Environmental assessment of packaged fresh chicken: A Life Cycle perspective on packaging and waste impacts	46
Giana NUNCIO Design and Analysis of Fat-based coatings used in the production of ice cream stick bars	49

Table of contents

Juliana PORRAS ALZATE The Role of Dynamic Shelf Life Labels in Consumers' Buying Decisions	50
Andrea ROJAS Study the impact of protectants to increase shelf life in dry product	56
Marie SAZERAC DE FORGE Analysis of public financing of food in Île-de-France	58
Wiktorija SIENNICA Improvement of the flavour profile of Philadelphia plant-based Cream Cheese and exploration and characterization of alternative vegan protein sources	61
Aswin SRIDHAR Experimental study of ice cream freezing	67
Maria Paola VARGAS CALLEJAS Towards a Circular Future: A Roadmap for Sustainable Industrial Packaging	68
Sreshtha VERMA Valorization of Agricultural By-products: Nanocellulose Barrier Films for Sustainable Food Packaging	74
Kawtar ZAAZAI Optimization and validation of a pilot-scale protocol for assessing the technological suitability of wheat flours in croissant production	76

Introduction

It is always a great pleasure to comment on the work of our FIPDes students and colleagues!

You are holding in your hands a great concentrate of the MSc. Thesis FIPDes adventure: the book of executive summaries. This book was edited over the summer thanks to the dedication of our students and the careful work of Lucile Deloince, who was in charge of the publication.

Why this book?

It is a tangible way to demonstrate the variety of topics covered by the FIPDes students in their MSc. theses, ranging from food engineering and packaging to reformulation, food nutrition, and ingredient evaluation. They take the perspective of sustainable food systems, spanning from pilot plants to public policies, and from by-product valorization to environmental assessment.

If you attended the 2025 FIPDes Day, this book contains the conference proceedings of the students' flash presentations and posters. Otherwise, this small book offers a taste of the cutting-edge research carried out in public and private laboratories across Europe, which the students had the opportunity to join during their MSc. Thesis internship.

Our best partners and collaborators will also receive this gift, which is a great way to keep track of FIPDes alumni, who will most probably be their future colleagues and employees.

Looking at the picture of the 2025 cohort brings back lots of memories...

One of the finest was the mentoring on an extraordinary FIPDes "Junior Project" on spatial food.

FIPDesers designed and realized amazing prototypes, and perhaps your grand-grandchildren will taste them en route to Mars?

From a closer perspective, a lot of work is waiting to be done by FIPDes graduates to improve food on Earth... now!



The innovative, cooperative, responsible and ethical mindset of our FIPDes alumni is therefore more than necessary. Looking at the work done during these 2 years of the FIPDes program and to their MSc. Thesis projects, I am happy to say that they are already making a significant contribution!

Congratulations to the 2025 FIPDes graduates!
Happy reading to all!

Comparatively Exploring the Effect of Yeast on Oven Spring Using Conventional and Ohmic Baking

**Juan Pablo
ADAME PATIÑO**

MEXICO



adame.juanp@gmail.com

Profile in a nutshell:

- MSc. Food Innovation and Product Design (FIPDes), specialization in Food Design and Engineering - AgroParisTech (France), TU Dublin (Ireland).
- BSc. Biotechnology Engineering, minor in Bioprocess Engineering - Tecnológico de Monterrey (Mexico).

Interests:

New product development, continuous improvement, quality assurance, food innovation, data analysis, project management.

Master Thesis hosting lab/company:

Baking Science and Nutrition R&D Team, Lesaffre Institute of Science and Technology

Master Thesis tutors:

Stéphanie ROUX, PhD

Introduction

Loaf volume is a key quality parameter in bread for consumers (Marshall, 1988). Most of the volume increase in a loaf of bread occurs within the first minutes of baking, during a phenomenon commonly known as “oven rise” or “oven spring” (Le-bail et al., 2011). Although no real-time measurements of oven spring have been cited in literature, current mathematical models suggest that the accelerated rate of production of CO₂ during the initial stages of baking and the subsequent expansion of entrapped CO₂ in the gluten network accounts for most of the effect (Zhang & Datta, 2006).

As the primary source of CO₂ during proofing and baking, yeast is thought to be a key formulation component affecting oven spring in pan bread. Furthermore, the metabolites produced by yeast during dough fermentation have been found to affect the rheological properties and extensibility of dough (Meerts et al., 2018; Jayaram, et al. 2014), which may in turn influence the evolution of loaf volume (Tietze et al., 2016). To better understand the impact of yeast on oven spring, an assortment of 12 commercially available strains used for different applications, including winemaking, brewery, bioethanol production, and breadmaking were tested. The gassing power and metabolite production of each strain were assessed, after which baking trials were conducted.

To aid in the real-time measurement of oven spring, a Dynamic Baking Camera (DBC) capable of following the changes of volume in bread inside a convection oven throughout the baking process was developed and implemented. Oven spring values were also measured inside an internally developed Electric Resistance Oven (ERO) capable of producing crustless bread through ohmic baking (Gally et al., 2016), maximizing loaf volume through the elimination of crust pressure (Zhang et al., 2007). The oven spring measurements of both baking methods were contrasted, and the resulting loaves of bread were characterized using texturometry and imaging techniques.

Research Objectives

The project aims to:

- Compare the oven spring measurements obtained with the dynamic baking camera to those obtained with the electric resistance oven.
- Analyse how these measurements relate to the properties of the yeast strain (gassing power and metabolite production), and the attributes of the resulting loaf of bread.

Strategy and Methodology

As detailed in figure 1, the experiment can be broadly divided into three stages.

Stage 1: Fermentative qualities are assessed on each strain.

- *Proofing efficiency* - Rate of CO₂ production per minute is measured in fermented dough.
- *Metabolite analysis* - Ethanol and glycerol is quantified from fermented dough samples.

Stage 2: Oven spring is measured during baking on two types of bread.

- *Conventional Bread Test* - Produced in a convection oven and measured with the DBC.
- *Crustless Bread Test* - Produced in the ERO and measured with infrared height sensors.

Stage 3: Bread loaves obtained from baking tests are characterized.

- *Volumetric Scanning* - Volume of bread loaf is measured after 2h of rest at 21°C
- *Bread Imaging* - Loaf is sliced, and each slice is scanned to characterize its gas cells.
- *Texture Profile Analysis* - A double compression test is conducted on each slice.




Figure 1. Experimental strategy followed throughout the project. The method used for each experiment is indicated between parenthesis for each case.

Results and Discussion

The fermentation time for each strain was calculated as the time required to produce 120ml of CO₂ as measured with a Risograph (National Manufacturing Co., USA). ANOVA treatment of the data reveals statistically significant differences between strains ($p=0.00$, $R^2=99.39\%$), with half of the quickest-fermenting strains being all used for breadmaking. Conversely, brewery, winemaking, and bioethanol production strains were all within the slowest 50% of strains (Table 1). Analysis of ethanol and glycerol concentrations revealed a consistent positioning of S7, S2, and S10 as the most productive and S3 and S8 as the least productive strains, with most breadmaking strains showing no significant difference from each other.

Yeast Strain	Application	Grouping ^a	Average Time (hh:mm:ss)	Coef. Variation (%)	Position ^b
S1	Breadmaking	EF	01:18:40	3,61	2
S2	Breadmaking	CD	01:44:50	7,35	8
S3	Breadmaking	B	02:07:10	0,23	10
S4	Breadmaking	EF	01:23:10	1,74	4
S5	Breadmaking	F	01:17:50	0,74	1
S6	Breadmaking	EF	01:21:50	1,96	3
S7	Breadmaking	EF	01:23:50	0,91	5
S8	Brewery	A	03:15:30	2,88	12
S9	Winemaking	D	01:36:40	2,6	7
S10	Bioethanol	C	01:50:50	2,48	9
S11	Non-Saccharomyces Brewery	A	03:14:10	1,19	11
ST ^c	Breadmaking	E	01:26:18	1,72	6

Table 1. List of yeast strains and their average fermentation time.

a: grouping as calculated with Tukey's Range Test (CI = 95%). b: positioning of strain from quickest to slowest. c: "ST" denotes experimental autocontrol strain.

Unlike the convection oven, which creates large temperature gradients that encourage the rapid expansion of entrapped CO₂ (Purlis & Salvadori, 2010), ohmic ovens were conceived to evenly heat the loaf resulting in a more uniform baking process (Gally et al., 2016). As a result, the loaf of bread expands gradually, only slowing down as the crumb sets, near the end of baking (Zhang & Datta, 2006), as opposed to the sharp volume increase observed in the case of convection ovens (Figure 2).




Figure 2. Evolution of bread loaf dimensions during baking.

A: volume change in a bread loaf fermented with strain S7 inside of the convection oven
B: height change in a bread loaf fermented with strain S7 inside of the ERO.

The sharp decrease in volume following oven spring in the convection oven trials deviates from previous experiments, resulting from the removal of bread improvers from the tested recipe. Work by Silva et al. (2022) illustrates that, at the tested temperature (200°C), the stress of gas expansion during oven spring can more easily rupture gluten cells, affecting volume and stability. Bread improvers help reduce this effect by decreasing the resistance to extension and increasing the maximum extensibility of dough (Tebben et al., 2018).




Figure 3. Interval plot of oven spring percentages (OVS%) per strain.

A: values measured in convection oven (pooled St. Dev. = 1.7)

B: values measured in ohmic oven (pooled St. Dev. = 1.43)

No significant difference in oven spring was found between strains in the convection oven tests, as opposed to the results obtained in the ohmic baking tests (Figure 3). Likewise, oven spring and fermentation time were found to be moderately correlated in the ohmic baking tests ($r=-0.615$, $p=0.00$), though not so in the convection oven tests. Research by Vandenbosch et al. (2025) suggests that yeast survivability and gas production rate under heat stress are important variables influencing oven spring, explaining the performance gap, as ohmic ovens allow yeast to more optimally produce CO_2 for longer (Gally et al., 2017).

In both cases, no relation between glycerol and ethanol concentrations to oven spring was found, though glycerol concentration showed a moderate correlation to final volume in both ohmic baking ($r=0.575$, $p=0.00$) and convection baking tests ($r=0.689$, $p=0.00$). Although both metabolites have been identified as important to ensure adequate proofing (Aslankoochi et al. 2015; Jayaram et al., 2014), organic acids have been found to specially contribute to the development of loaf volume (Su et al., 2019), highlighting the need to consider these metabolites for further studies relating to oven spring.




Figure 4. PCA loading plot (convection oven tests).




Figure 5. PCA score plot (convection oven tests).

Principal component analysis of the bread characterization parameters revealed springiness, brightness, cell elongation, and number of gas cells to be the most correlated to oven spring in ohmic baking trials, though only marginally so in convection oven trials (Figure 4) owing to the sharp volume collapse observed in the latter case which effectively undoes the effect of oven spring. Meanwhile, hardness and chewiness were the most strongly related to bread volume in both tests, matching observations in literature (Dessev et al., 2020). In the convection oven trials, the brewing strains S8 and S11 spread away from the main cluster of data in the score plot (Figure 5). This trend is also observable in the ohmic baking trials, though to a lesser extent.

Conclusion

Techniques like ohmic baking may be helpful to evaluate the potential of different yeast strains with regards to oven spring, but the performance under such conditions does not necessarily reflect the performance observed when yeast is implemented in traditional baking processes. In this respect, the Dynamic Baking Camera has been proven to be a helpful and innovative tool to further validate yeast performance under practical conditions. Moreover, the study of oven spring may also benefit from additional techniques such as dynamic rheological measurements, yeast survivability tests, and organic acid profiles.

References

- Aslankoohi, E., Rezaei, M. N., Vervoort, Y., Courtin, C. M., & Verstrepen, K. J. (2015). Glycerol Production by Fermenting Yeast Cells Is Essential for Optimal Bread Dough Fermentation. *PLOS ONE*, 10(3), e0119364. <https://doi.org/10.1371/journal.pone.0119364>
- Dessev, T., Lalanne, V., Keramat, J., Jury, V., Prost, C., & Le-Bail, A. (2020). Influence of Baking Conditions on Bread Characteristics and Acrylamide Concentration. *Journal of Food Science and Nutrition Research*, 3(4), 291–310.
- Gally, T., Rouaud, O., Jury, V., Havet, M., Ogé, A., & Le-Bail, A. (2017). Proofing of bread dough assisted by ohmic heating. *Innovative Food Science & Emerging Technologies*, 39, 55–62. <https://doi.org/10.1016/j.ifset.2016.11.008>
- Gally, T., Rouaud, O., Jury, V., & Le-Bail, A. (2016). Bread baking using ohmic heating technology; a comprehensive study based on experiments and modelling. *Journal of Food Engineering*, 190, 176–184. <https://doi.org/10.1016/j.jfoodeng.2016.06.029>
- Jayaram, V. B., Rezaei, M. N., Cuyvers, S., Verstrepen, K. J., Delcour, J. A., & Courtin, C. M. (2014). Ethanol at Levels Produced by *Saccharomyces cerevisiae* during Wheat Dough Fermentation Has a Strong Impact on Dough Properties. *Journal of Agricultural and Food Chemistry*, 62(38), 9326–9335. <https://doi.org/10.1021/jf502547a>
- Le-bail, A., dessev, T., Leray, D., Lucas, T., Mariani, S., Mottollese, G., & Jury, V. (2011). Influence of the amount of steaming during baking on the kinetic of heating and on selected quality attributes of bread. *Journal of Food Engineering*, 105(2), 379–385. <https://doi.org/10.1016/j.jfoodeng.2011.03.001>
- Marshall, A. R. (1988). Loaf Volume Measurement. *IEE Colloquium on Measurements We Couldn't Make Without a Micro*, 5–6. <https://ieeexplore.ieee.org/document/696041>
- Meerts, M., Ramirez Cervera, A., Struyf, N., Cardinaels, R., Courtin, C. M., & Moldenaers, P. (2018). The effects of yeast metabolites on the rheological behaviour of the dough matrix in fermented wheat flour dough. *Journal of Cereal Science*, 82, 183–189. <https://doi.org/10.1016/j.jcs.2018.06.006>

Purlis, E., & Salvadori, V. O. (2010). A moving boundary problem in a food material undergoing volume change – Simulation of bread baking. *Food Research International*, 43(4), 949–958. <https://doi.org/10.1016/j.foodres.2010.01.004>

Silva, T. H. L., Monteiro, R. L., Salvador, A. A., Laurindo, J. B., & Carciofi, B. A. M. (2022). Kinetics of bread physical properties in baking depending on actual finely controlled temperature. *Food Control*, 137, 108898. <https://doi.org/10.1016/j.foodcont.2022.108898>

Su, X., Wu, F., Zhang, Y., Yang, N., Chen, F., Jin, Z., & Xu, X. (2019). Effect of organic acids on bread quality improvement. *Food Chemistry*, 278, 267–275. <https://doi.org/10.1016/j.foodchem.2018.11.011>

Tebben, L., Shen, Y., & Li, Y. (2018). Improvers and functional ingredients in whole wheat bread: A review of their effects on dough properties and bread quality. *Trends in Food Science & Technology*, 81, 10–24. <https://doi.org/10.1016/j.tifs.2018.08.015>

Tietze, S., Jekle, M., & Becker, T. (2016). Possibilities to derive empirical dough characteristics from fundamental rheology. *Trends in Food Science & Technology*, 57, 1–10. <https://doi.org/10.1016/j.tifs.2016.08.016>

Vandenbosch, S., De Bondt, Y., Steensels, J., Verstrepen, K., & Courtin, C. M. (2025). The thermotolerance of industrial yeast strains in a dough matrix determines their impact on the oven rise during bread baking. *Food Chemistry*, 491, 145151. <https://doi.org/10.1016/j.foodchem.2025.145151>

Zhang, J., & Datta, A. K. (2006). Mathematical modeling of bread baking process. *Journal of Food Engineering*, 75(1), 78–89. <https://doi.org/10.1016/j.jfoodeng.2005.03.058>

Zhang, L., Lucas, T., Doursat, C., Flick, D., & Wagner, M. (2007). Effects of crust constraints on bread expansion and CO₂ release. *Journal of Food Engineering*, 80(4), 1302–1311. <https://doi.org/10.1016/j.jfoodeng.2006.10.008>

Performance Evaluation of Sugar Alternatives in No Added Sugar Muffins

**Muskan
AGARWAL**

INDIA



muskanagarwal713@gmail.com

Profile in a nutshell:

- Master of Science in Food Innovation and Product Design
- Bachelor of Food Science and Management, University of Madras, India

Interests:

Food innovation, Cooking, Travel

Master Thesis hosting lab/company:

Puratos Group, Dilbeek, Belgium

Master Thesis tutors:

Prof. Paola Vitaglione

Excessive sugar consumption is linked to adverse health outcomes, prompting global efforts to reduce added sugars in food products. In bakery applications, sugar plays multifaceted roles beyond sweetness, including texture, volume, and shelf-life enhancement. Reformulating baked goods like muffins without compromising sensory and structural quality remains a significant challenge.

This thesis aimed to evaluate the performance of selected polyol and fiber based sugar alternatives in a no added sugar (NAS) muffin recipe, assessing their impact on physical, textural, and sensory attributes. Studies done as a part of this thesis showed that various physio-chemical factors had a high effect on the overall acceptability of a NAS muffin. A consumer panel evaluated the muffins on a Just About Right (JAR) scale to determine sweetness perception in the finished product.


There was therefore a hypothesis formed about the use of polyols and fibre as a potential sugar replacement in bakery products and with the help of this study, a benchmarking was set in place to extend the range of Healthy & Well-Being products under sugar reduction in Patisserie.

CONFIDENTIAL TOPIC

Optimisation of the Technological and Organoleptic quality of lean bread enriched with seeds and grains

**Jenipher
ALUM**

UGANDA



alumjenipher21@gmail.com

Profile in a nutshell:

- Master of Science in Food Innovation and Product Design
- Bachelor of Science in Food Science and Technology

Interests:

Sustainable Food product development and Safety, Alternative Proteins, Food data modelling.

Master Thesis hosting lab/company:

Puratos HQ, Belgium

Master Thesis tutors:

Mauriello GianLuigi
Vanhuele Isabel

The study involved the incorporation of grains and seeds which are reported to increase bread freshness, nutrition and flavours of lean bread, but also may limit its dough handling and final quality. These hinder their feasibility in bakery operations.

So, the goal was to optimise enriched bread for similar or better dough consistency, volume and softness to the control. Hydration values, grain addition timing and grain dosage were phase by phase evaluated to achieve this goal.

Hydration levels adjustment was helpful though initially didn't significantly and positively improve dough handling. Subsequent water level variation achieved optimal dough handling and bread quality significantly similar to the control. Introducing grains before the end of mixing improved bread quality. Lower grain dosage produced bread with most physicochemical properties similar to the control bread.

The study results indicated the successful enrichment of bread with the grains and seeds products. The insights obtained will be useful for launch of bread enriched with the scope of grains and seeds products that have improved freshness, volume and dough handling.

CONFIDENTIAL TOPIC

Towards the use of sustainable alternative caseins: optimization of the stretching properties of cheese analogues hybrid matrices

**Blandine
BOUCHELET de
VENDEGIES**

FRANCE



blandinebdev@gmail.com

Profile in a nutshell:

- MSc. Food Innovation and Product Design (FIPDes) with specialization in Healthy Food Design at UNINA (Italy)
- Bachelor of Life & Environmental Sciences and Master of Food & Biomolecules Engineering at AgroParisTech (France)

Interests:

Food product development, Food innovation, Formulation, Nutrition, Fermentation processes, Process improvement, and Project management.

Master Thesis hosting company:

Food Physics team, Group Bel Applied Research

Master Thesis tutors:

Prof. Chiara NITRIDE
Dr. Thibault LOISELEUX

Milk and dairy products have long been key sources of high-quality nutrients, with cheese standing out for its cultural and functional versatility. Today, global demand for dairy is rising, especially in developing countries, while environmental and ethical concerns are pressuring the dairy sector to evolve. Plant-based cheese substitutes (PBCS), though emerging, still fall short in mimicking the sensory and functional qualities of traditional cheese, such as meltability and stretchability, because of the many differences in structure and functionalities between plant-based and dairy proteins.

Precision fermentation offers there a promising solution by producing animal-free dairy proteins with identical structures to their natural counterparts. In this context, the Bel Group, a global leader in branded cheese committed to sustainable innovation, partnered with the French start-up Standing Ovation (SO) to produce and use alternative proteins to develop vegan cheese analogs with good organoleptic properties, improved nutritional value and reduced environmental impact.

CONFIDENTIAL TOPIC

Physicochemical Evaluation of Crackers Enriched With Mealworm (*T. molitor*) Meal: Influence of Nutrient Composition and Storage

**Constanza
CABALLERO**

MEXICO



constanzacaballero99@gmail.com

Profile in a nutshell:

- MSc. Food Innovation and Product Design (FIPDes) with specialization in Healthy Food Design, AgroParisTech (France), TU Dublin (Ireland), UNINA (Italy)
- Bachelor of Biotechnology Engineering with concentrations in Biocatalysis and Food Science, Tecnológico de Monterrey (Mexico)

Interests:

Research and Development, Food Innovation, Novel Foods, Nutrition, Traveling, Art

Master Thesis hosting lab/company:

Max Rubner Institute (Germany), Department of Food Technology and Bioprocess Engineering

Master Thesis tutors:

Prof. Pasquale Ferranti, Dr. Kathleen Oehlke, M.Sc. Rebecca Rüsck

Introduction

Mealworms (*Tenebrio molitor*) are edible insects approved in Europe as Novel Foods since June 2021 (Regulation (EU) 2021/882). They are valued for their high-quality protein, essential amino acids, and healthy fats, including omega-3 and omega-6 fatty acids, which are comparable to those found in meat and fish (Djouadi et al., 2022; van Huis et al., 2013).

Due to these nutritional benefits, mealworms are gaining attention as food ingredients. However, their nutritional composition can vary significantly depending on factors such as diet and weight (Kröncke & Benning, 2023; Toviho & Bársony, 2022). These inconsistencies may impact the quality of the final food products in which they are used. On the other hand, this variability could also be used advantageously to tailor the requirements of a product, for instance, to increase protein or fat content depending on the formulation goals.

This study aims to analyse how three different nutritional compositions of mealworms (resulting from different diets and individual weights) affect the quality of crackers enriched with 15% mealworm meal. The parameters evaluated include colour, dimensions, water activity, moisture content, texture, and lipid oxidation during storage.



Figure 1. Processing of mealworms into meal to be introduced in crackers.

Methodology

Differences in the nutritional composition of mealworms were achieved through different feed and individual mealworm weights: Std_80 (wheat bran, 80 mg), StdA_80 (wheat bran + Chlorella + spelt husks, 80 mg), and LPHF_100 (wheat bran + rice bran + apple pomace, 100 mg). This was conducted prior to the present study.

Crackers were evaluated at four timepoints (24 hours (t0), 7 days (t1), 28 days (t2), and 42 days (t3) after baking) during an accelerated storage test at 40°C.

Colour was measured with a colorimeter using Lab* values, from which the Browning Index (BI) and Colour Change (ΔE) were calculated. Dimensions (length, width, and thickness) were measured using a digital caliper, and the spread ratio was subsequently calculated. Moisture content was determined using a halogen moisture analyser, while water activity was measured with a hygrometer.

Texture was assessed using a Texture Analyser with a three-point bend rig (Figure 3.). Lipid oxidation was evaluated with the thiocyanate method, which measures hydroperoxide concentration in fat extracted from the crackers (Figure 4.).




Figure 2. Process Diagram



Figure 3. Texture Analyser with three-point bend rig




Figure 4. Sample during Thiocyanate method

Results and Discussion

Colour: Mealworm crackers were darker (lower L* values, and higher BI values) compared to the control, mainly due to the natural pigment of insect meal and increased Maillard reaction due to higher protein content (Djouadi et al., 2022). No significant difference (considering colour change, ΔE) was observed between mealworm treatments (Figure 5.).



Figure 5. Different treatments of crackers produced.

Dimensions: Control crackers were thicker and showed more air bubbles, likely due to a stronger gluten network (Figure 5.). Mealworm particles and proteins disrupted the gluten network formation (Xie et al., 2022) making the crackers thinner.

%MC and aw: Mealworm crackers had lower %MC and aw, due to reduced water and gas retention from weakened gluten network in mealworm dough (Djouadi et al., 2022; Xie et al., 2022). All treatments showed aw values below the microbial stability threshold (0.6) and within the typical cracker range (0.01–0.3) (Nakamura et al., 2012) (Figure 6.).




Figure 6. MC% and aw of crackers at t0.

Texture: Control crackers were harder and less fracturable, while mealworm crackers were softer and more fracturable. This indicates a higher crispiness in mealworm crackers, which is a desired textural attribute. This is likely due to the higher fat content in mealworm crackers, which weakened the gluten network, contributing to a more tender structure, reduced moisture and enhanced crispiness. This was also observed by Djouadi et al. (2022).

Lipid oxidation: Mealworm crackers showed better oxidative stability, possibly due to antioxidant effects of the mealworm meal (Figure 7.). Mealworm crackers had higher oleic acid and lower linoleic acid compared with the control, improving oxidative stability. Adding to this, proteins (Elias, Kellerby, & Decker, 2008), reducing sugars (Vu et al. 2020), and Maillard reaction products (melanoidins) (Baek et al. 2019) from the mealworm meal could have also contributed to the observed antioxidant effect. This oxidative stability is desired for avoiding early rancidity and therefore extending the product's shelf life.




Figure 7. Lipid oxidation of crackers during storage.

Conclusion

The enrichment of crackers with mealworm meal can improve the nutritional profile, crispiness and oxidative stability of crackers, improving shelf life and quality of the product. However, no significant differences were observed in the quality parameters among the different mealworm treatments, indicating that differences in nutritional compositions did not have an impact on the quality of the crackers with 15% mealworm meal.

Resources

- Baek, M., Kim, M. A., Kwon, Y. S., Hwang, J. S., Goo, T. W., Jun, M., & Yun, E. Y. (2019). Effects of processing methods on nutritional composition and antioxidant activity of mealworm (*Tenebrio molitor*) larvae. *Entomological Research*, 49(6), 284–293. <https://doi.org/10.1111/1748-5967.12363>
- Djouadi, A., Sales, J. R., Carvalho, M. O., & Raymundo, A. (2022). Development of Healthy Protein-Rich Crackers Using *Tenebrio molitor* Flour. *Foods*, 11(5), 702. <https://doi.org/10.3390/foods11050702>
- Elias RJ, Kellerby SS, Decker EA. Antioxidant activity of proteins and peptides. *Crit Rev Food Sci Nutr*. 2008 May;48(5):430-41. doi: 10.1080/10408390701425615. PMID: 18464032.
- European Commission. (2021). Commission Implementing Regulation (EU) 2021/882 of 1 June 2021 authorising dried yellow mealworm (*Tenebrio molitor*) larvae as a novel food under Regulation (EU) 2015/2283 of the European Parliament and of the Council. *Official Journal of the European Union*, L 198, 79–88.
- Kröncke, N., & Benning, R. (2023). Influence of Dietary Protein Content on the Nutritional Composition of Mealworm Larvae (*Tenebrio molitor* L.). *Insects*, 14(3), 261. <https://doi.org/10.3390/insects14030261>
- Nakamura, S., Suzuki, D., Kitadume, R., & Ohtsubo, K. (2012). Quality evaluation of rice crackers based on physicochemical measurements. *Bioscience, Biotechnology, and Biochemistry*, 76(4), 794–804. <https://doi.org/10.1271/bbb.110931fdjouadi>
- Toviho, O. A., & Bársony, P. (2022). Nutrient composition and growth of yellow mealworm (*Tenebrio molitor*) at different ages and stages of the life cycle. *Agriculture*, 12(11), 1924. <https://doi.org/10.3390/agriculture12111924>
- van Huis, A., van Itterbeeck, J., Klunder, H., Mertens, E., Halloran, A., Muir, G., & Vantomme, P. (2013). Edible insects: Future prospects for food and feed security. *FAO Forestry Paper 171*. Food and Agriculture Organization of the United Nations.
- Vu, T. P., He, L., McClements, D. J., & Decker, E. A. (2020). Effects of water activity, sugars, and proteins on lipid oxidative stability of low moisture model crackers. *Food Research International*, 130, 108844. <https://doi.org/10.10>
- Xie, X., Yuan, Z., Fu, K., An, J., & Deng, L. (2022). Effect of Partial Substitution of Flour with Mealworm (*Tenebrio molitor* L.) Powder on Dough and Biscuit Properties. *Foods*, 11(14), 2156. <https://doi.org/10.3390/foods11142156>

Thermal Processing Effects on Pulse Matrix: A Multiscale Approach

**Charlotte
DELATTRE**

FRANCE



charlottedelattre9@gmail.com

Profile in a nutshell:

- MSc. Food Innovation and Product Design (FIPDes) at AgroParisTech (France), TU Dublin (Ireland) with specialization in Healthy Food Design at University of Naples (Italy)
- Engineering Degree from AgroParisTech (following preparatory classes CPGE)

Interests:

Complex matrix study, Raw material transformation, R&D, Plant-based alternatives, Culinary heritage

Master Thesis hosting lab/company:

Danone Research & Innovation, Advanced Technology Ingredients, Paris-Saclay, France

Master Thesis tutors:

Paola VITAGLIONE (UNINA, ITALY)

Laurence DE WAELE (DANONE, FRANCE)

Introduction

With the rising demand for sustainable and nutritious plant-based beverages, pulses are gaining attention as alternatives to soy. Pulses are particularly attractive due to their high protein content, low allergenicity, and favorable agronomic profile. The use of whole pulses, rather than protein isolates or concentrates, preserves nutritional integrity but introduces processing challenges due to their complex structure. It affects the final product's texture, stability, and sensory attributes. Moreover, off-flavors commonly associated with pulses, such as beany or grassy notes, further limit their acceptance in beverage applications. This thesis investigates how thermal treatments, with a focus on high-temperature pretreatment steps, affect the physicochemical, functional and sensory properties of beverages made from whole pulses.

Unlike conventional approaches that rely on fractionated ingredients, this study adopts a multiscale perspective to evaluate the transformation of the native matrix during processing. The study aims to:

- Understand how thermal treatments influence protein characteristics, starch behavior, and functional properties (e.g., foaming, emulsification).
- Use a multiscale approach to analyze changes from molecular to macroscopic levels.
- Provide insights for optimizing processing conditions to improve product quality.

CONFIDENTIAL TOPIC

Impact and Lifecycle of New Barrier Polymer in Beverage Carton Recycling

A Lab-Scale Experimental Study

**Oğuzhan
DURSUN**

TURKEY



oguzhndursun@gmail.com

Profile in a nutshell:

- MSc. Food Innovation and Product Design (FIPDes) with specialization in Food Packaging Design and Logistics, Lund University (Sweden), AgroParisTech (France), TU Dublin (Ireland)
- BSc in Food Engineering, Ankara University (Turkey)

Interests:

Sustainability, Product & Packaging Development, Entrepreneurship, Innovation, Graphic Design

Master Thesis hosting lab/company:

Tetra Pak Packaging Solutions AB, Lund, Sweden

Master Thesis tutors:

Klas Hjort, Lund University
Davide Capucci, Tetra Pak

Introduction

The global shift toward sustainable packaging has accelerated the development of new materials for beverage cartons. These multilayer systems—typically paperboard, polyethylene (PE), and aluminum—offer strong protection but are hard to recycle due to the difficulty of separating layers (Bauer et al., 2021). To improve recyclability, the industry is testing alternative barrier layers that retain functionality while being recycling-friendly. One promising option is polyvinyl alcohol (PVOH), a water-soluble synthetic polymer known for its film-forming ability, low oxygen permeability, and biodegradability (Solaro et al., 2000).

Although PVOH is well studied in other industries like pharmaceuticals and textiles, its solubility and detectability in beverage carton recycling—particularly during hydropulping—remain poorly understood. At present, no standardized methods are available for detecting or quantifying PVOH in recycling outputs such as process water or PolyAl residues.

This study addresses the methodological gap by experimentally evaluating the solubility and recycling behavior of PVOH under lab conditions that simulate hydropulping. It also proposes a UV-Vis spectrophotometric method for detecting trace levels of PVOH in different streams. By investigating how variables like coating thickness and temperature affect solubility, the study contributes to better understanding PVOH's role in recycling systems and supports the design of more recyclable multilayer packaging.




Figure 1. Two interconnected phases of Experimental Design

This study followed a two-phase experimental approach to investigate the recyclability and detectability of polyvinyl alcohol (PVOH) in beverage cartons. The first phase focused on developing a reliable method for detecting and quantifying PVOH in aqueous solutions. The Finley colorimetric method was selected, which forms a colored complex between iodine, boric acid, and PVOH, showing peak absorbance at 675 nm (Finley, 1961; Pritchard & Akintola, 1972). A calibration curve was established using UV-Vis spectrophotometry, and the method's accuracy was validated by calculating the limit of detection (LOD) and limit of quantification (LOQ) based on blank sample measurements (Thomsen et al., 2003).

In the second phase, the study focused on evaluating the behavior of PVOH under simulated hydropulping conditions, with attention to its solubility and detectability in recycling streams such as PolyAl residue and process water. To assess recyclability, key variables—including coating thickness, drying temperature, and immersion time—were systematically varied to examine their influence on PVOH performance under conditions replicating industrial repulping. PET films were coated with PVOH on different thicknesses and cured at either 25 °C overnight or 100 °C for 12 minutes to produce samples. These films were immersed in distilled water at 20 °C or 45 °C and stirred at 900 rpm to simulate hydropulping turbulence. This setup allowed for isolation of individual factors affecting PVOH dissolution.

Moreover, Fourier-transform infrared spectroscopy (FT-IR) and Differential Scanning Calorimetry (DSC) were employed to assess the presence of PVOH in both aqueous and solid fractions, and to validate the results obtained from UV-Vis spectrophotometry. A gravimetric approach was also used to estimate the amount of polyvinyl alcohol coated on PET films.

Results

Results were obtained through a stepwise approach, starting with the development of a spectrophotometric method to detect PVOH in aqueous solutions. A calibration curve using known PVOH concentrations complexed with iodine and boric acid showed a strong linear relationship ($R^2 = 0.9987$), confirming the method's reliability with a detection limit of 0.06 mg/L.




Figure 2. Calibration curve of PVOH solutions

Results showed that PVOH dissolves rapidly in water, with the majority of dissolution occurring within the first few minutes—particularly during the initial 60 seconds of immersion. Elevated water temperatures enhanced the rate of dissolution by increasing molecular mobility and film porosity, while films dried at higher temperatures (100°C) showed slower dissolution rate. Thicker coatings also slowed dissolution, as water penetration into the denser polymer layer was more limited. Subsystem tests confirmed that both temperature and coating thickness are important factors influencing solubility.

UV-Vis spectrophotometry and gravimetric analysis produced consistent results, with closely matching trends, confirming the accuracy and reliability of the method.




Figure 3. PVOH Dissolution During the First 300 Seconds of Immersion




Figure 4. Comparison of Spectrophotometric and Gravimetric Methods

In CEPI recyclability trials, PVOH was primarily detected in the process water rather than in the PolyAl residue, confirming its dissolution pathway during simulated hydropulping. These findings support the potential recyclability of water soluble barrier layers, especially since the concentration of polymer on the polyAl fraction remained well below the 1% limit set by Design for Recycling guidelines (RecyClass, 2024). However, one notable challenge emerged in the detection phase: residual starch from the paperboard also formed colored complexes with iodine, resulting in overlapping absorbance signals that interfered with accurate PVOH quantification.

Conclusion

This study successfully developed a lab-scale detection method for PVOH using UV-Vis spectrophotometry, demonstrating strong linearity and sensitivity. The Finley method proved suitable for low-concentration detection and was effectively used throughout the experiments. The developed UV-Vis spectrophotometric method—based on the Finley iodine is a fast, low-cost, and industry-adaptable approach for detecting PVOH in aqueous streams. Its simplicity and reproducibility make it suitable for routine lab applications. Subsystem and gravimetric tests showed that PVOH dissolution increases with temperature and is affected by coating thickness and drying conditions. CEPI recyclability tests confirmed that PVOH dissolves into process water, validating the detection protocol.

However, the study also identified limitations, particularly regarding the interference caused by starch present in paperboard layers. This interference can lead to overestimated PVOH concentrations due to overlapping absorbance signals in UV-Vis readings. Therefore, future research should incorporate the proposed correction strategies—such as the dual-wavelength method, acid hydrolysis, or enzymatic treatment—to improve measurement accuracy in more complex, real-world recycling matrices.

Overall, this research contributes valuable insights into the behavior of water-soluble barrier materials like PVOH and provides a foundation for developing standard detection and recyclability assessment methods that can support material design and packaging innovation.

References

- Bauer, A.-S., Tacker, M., Uysal-Unalan, I., Cruz, R. M. S., Varzakas, T., & Krauter, V. (2021). Recyclability and Redesign Challenges in Multilayer Flexible Food Packaging—A Review. *Foods*, 10(11), Article 11. <https://doi.org/10.3390/foods10112702>
- Finley, J. H. (1961). Spectrophotometric determination of polyvinyl alcohol in paper coatings. *Analytical Chemistry*, 33(13), 1925–1927. <https://doi.org/10.1021/ac50154a044>
- Pritchard, J. G., & Akintola, D. A. (1972). Complexation of polyvinyl alcohol with iodine: Analytical precision and mechanism. *Talanta*, 19(7), 877–888. [https://doi.org/10.1016/0039-9140\(72\)80256-X](https://doi.org/10.1016/0039-9140(72)80256-X)
- RecyClass. (2024). Technical Review of PVOH Applications – Compatibility with Recycling. <https://recyclclass.eu/wp-content/uploads/2025/01/TechnicalReview-PVOH-v2.pdf>
- Solaro, R., Corti, A., & Chiellini, E. (2000). Biodegradation of poly(vinyl alcohol) with different molecular weights and degree of hydrolysis. *Polymers for Advanced Technologies*, 11(8–12), 873–878. [https://doi.org/10.1002/1099-1581\(200008/12\)11:8/12<873::AIDPAT35>3.0.CO;2-V](https://doi.org/10.1002/1099-1581(200008/12)11:8/12<873::AIDPAT35>3.0.CO;2-V)
- Thomsen, V., Schatzlein, D., & Mercuro, D. (2003). Limits of detection in spectroscopy. *Spectroscopy (Santa Monica)*, 18, 112–114.

Quantification of Yeast Metabolites in Dough

**Julio Alberto
GARCIA DOMINGUEZ**

MEXICO



julio_do@outlook.com

Profile in a nutshell:

- MSc. Food Innovation and Product Design with specialization in Food Design & Engineering.
- BSc. Biochemical Engineering.
- Background in supply chain management, packaging production, and quality assurance, complemented by experience in academia.

Interests:

Food fermentation, packaging innovation, culinary arts, photography and design.

Master Thesis hosting lab/company:

Lesaffre Institute of Science and Technology (LIST) - R&D Team Lille, France

Master Thesis tutors:

Mohammad Rezaei
Maude Dufour

Introduction

Yeast dough fermentation is a crucial step in the breadmaking process. The fermentative activity of *Saccharomyces cerevisiae* during this stage plays a vital role in determining the final bread characteristics (volume, aroma, rheology).

Despite significant research on the relationship between fermentation primary metabolites and textural changes in bread, more recent discoveries on the effects of secondary metabolites and their impact on the dough matrix have raised the concern that the effect and production rate of each compound has yet to be fully elucidated.

By assessing the metabolite production of *S. cerevisiae*, we can gain deeper insight into how these compounds shape bread characteristics. It is for this reason that a fully comprehensive analysis of the current analytical methods and their validity had to be performed.

CONFIDENTIAL TOPIC

Mono Material Lid Film Selection for Ready Meals

**Ana Maria
HENAO TOBON**

COLOMBIA/ PORTUGAL



anishenaot@gmail.com

Profile in a nutshell:

- M.Sc. in Food Innovation and Product Design with a specialization in Food Packaging Design and Logistics.
- Postgraduate degree in Chemical and Bioprocess Design
- B.Sc. in Process Engineering
- +5 years of Industry experience in R&D and Project Management: Product and Packaging Development

Interests:

Innovation, Sustainability, Business, and Marketing Strategies, Cross-functional Collaboration and Agile Methodologies. Traveling, coffee, food tasting, and learning languages

Master Thesis hosting lab/company:

Micvac, Gothenburg, Sweden

Master Thesis tutors:

Lars Palms
Uli Hose Pastor

Introduction

Sustainability has become a key driver of innovation in packaging and materials, fueled by rising environmental awareness and stricter regulations, like the Packaging and Packaging Waste Regulation (PPWR). Proposed by the European Commission, the PPWR aims to reduce packaging waste, improve recyclability, and support a circular economy (European Commission, 2022). One major focus is the shift from multi material packaging, structures made of several different plastic layers to mono material alternatives, which are made primarily from a single type of polymer such as polypropylene (PP). Mono materials are easier to sort and recycle using existing systems (Rizzo et al., 2024), while multi materials are difficult and costly to process, often ending up in landfill or incineration (Soares et al., 2022). This transition supports the creation of high-quality recycled materials and reduces environmental impact (Gonçalves et al., 2024).

This industry shift presents challenges for high-performance applications like microwaveable ready meals, where packaging must withstand cooking and reheating without compromising safety and food quality. Micvac, a company specializing in ready-meal packaging, has already transitioned its tray and valve to mono material PP, but the multilayer lid film remains a barrier to full recyclability (Micvac, 2024b). This thesis focuses on selecting a suitable mono material PP lid film for the Micvac FlexProcess™, a system where food is sealed, cooked in-pack using microwave energy, and later reheated by the consumer. The lid must seal securely, expand under steam (balloon), maintain vacuum after cooling, and open safely, all while working together with the tray and valve to ensure product safety and performance. Completing this transition would further position the company as a leader in sustainable innovation within the ready-meal sector.

Research Objective

Identify and validate a suitable mono material polypropylene (PP) lid film for use in the Micvac FlexProcess™ packaging system.

Research Questions

- 1.What are the essential design criteria for a mono material PP film in the Micvac FlexProcess™ package?
- 2.What critical parameters must be considered to validate the performance of the new lid film?
- 3.How do the available PP films compare in terms of the critical parameters?
- 4.What methodology can be used to develop a selection matrix for identifying the most suitable PP film?

Methodology

Five mono-material PP film candidates (M2, M20, M21, M22, M23) from three different suppliers were selected based on prior company screening, technical potential, and availability. Figure 1 illustrates the critical performance parameters used to evaluate these candidates throughout the Micvac FlexProcess™, which also served as key design criteria in this thesis. These parameters, such as sealing performance, processability, and peelability, were identified through literature review, supplier input, and internal screening. They were systematically assessed using a loop-based methodology, beginning with a Design of Experiments (DoE) on one film candidate (M20) to explore sealing behavior by evaluating internal pressure resistance. Once a minimum pressure threshold was established, this benchmark guided streamlined testing of the remaining films. The evaluation integrated both lab-based testing and tunnel trials under near-industrial conditions, along with consumer tests focusing on user-facing attributes such as peelability and ease of opening. Continuous feedback from suppliers and internal stakeholders supported the interpretation of results. A final selection matrix, based on Ulrich and Eppinger’s method, facilitated comparison of candidates across technical and practical dimensions, ultimately guiding the identification of the most suitable film.




Figure 1. Overview of critical performance parameters evaluated across the Micvac FlexProcess™.

Results

RQ1 What are the essential design criteria for a mono material PP film in the Micvac FlexProcess™ package? Two main design criteria were established: **product requirements and process compatibility**. From the product perspective, the film must ensure food safety, user-friendly opening, and product integrity throughout storage and reheating. From a process standpoint, it must withstand high temperatures during sealing, microwave cooking, and reheating, while allowing controlled steam expansion (ballooning) and maintaining a vacuum seal after cooling

RQ2 What critical parameters must be considered to validate the performance of the new lid film? These needs were translated into six critical parameters: **sealing performance, pressure resistance, mechanical properties, processability, reheating performance and peelability**, which together guide the evaluation and selection of suitable PP lid films.

RQ3 How do the available PP films compare in terms of the critical parameters?

Lab Tests

- M22 performed best overall, with good sealing, ballooning, vacuum retention, and user-friendly peelability; except for reheating performance with popping events.
- M20 had good mechanical and thermal stability, but lower performance in reheating
- Other films (M2, M21, M23) had issues such as poor seal strength, excessive stiffness, or poor peel profiles
- All candidate films showed peel forces within acceptable user limits (15- 25N) (Nilmanee, Somporn, 2022). M22 offered the easiest opening (8.4 N) with smooth peeling.

Tunnel Tests (Figure 2)

- M22 exhibited satisfactory behavior (Figure 3), with pronounced ballooning, smooth valve application, and less than a 5% defect (trays with no vacuum). M20 had a poor performance, with most of the trays without vacuum (light blue trays).




Figure 2. Parallel Comparison of Tunnel Performance for M22 and M20




Figure 3. M22 Vacuum appearance at the tunnel exit

RQ4 What methodology can be used to develop a selection matrix for identifying the most suitable PP film? The Ulrich and Eppinger method was chosen for its structured and objective approach to decision-making, allowing complex trade-offs to be evaluated transparently. A weighted matrix was created to compare one candidate per supplier based on three criteria: Functionality (63%), Financial (25%), and Supplier related factors (12%), and having the current film as baseline.

Conclusions

- **The study successfully identified M22 as the most promising mono-material PP lid film for the Micvac FlexProcess™.** Further improvements need to be made to improve seal strength after processing and during reheating.
- The Ulrich & Eppinger method enabled objective scoring of both quantitative data (seal strength, pressure resistance, ballooning, and peel ability) and qualitative factors (consumer usability). Optimal film choice depends on balancing process performance, seal integrity, and user experience rather than relying on a single property.
- Process window and robustness are very challenging with Mono materials; they are smaller and more sensitive to changes.
- Confidentiality restrictions limited access to precise seal layer compositions and material formulations.

References

- European Commission. (2022, June 22). Green Deal: Key to a climate-neutral and sustainable EU.Topics|EuropeanParliament.<https://www.europarl.europa.eu/topics/en/article/20200618ST081513/green-deal-key-to-a-climate-neutral-and-sustainable-eu>
- Gonçalves, A., Henriques, E., & Ribeiro, I. (2024). Towards plastics circular economy: Sustainability assessment of mono-material design for recycling. *Procedia CIRP*, 122, 401–406. <https://doi.org/10.1016/j.procir.2024.01.058>
- Micvac. (2024b). Sustainability – Micvac. <https://www.micvac.com/our-company/sustainability>
- Nilmanee, S. (2022). Developing prototypes of the assistant opener of packaging for consumer accessibility. *Journal of Graphic Engineering and Design*, 14(3), 27–36. <https://doi.org/10.24867/JGED-2023-3-027>
- Rizzo, M. V., Carlo Tancredi, G. P., & Vignali, G. (2024). The Recycling Technologies of Mono-material and Multilayer Plastic Film: A Descriptive Literature Review. *IFAC-PapersOnLine*, 58(19), 469–474. <https://doi.org/10.1016/j.ifacol.2024.09.256>
- Soares, C. T. de M., Ek, M., Östmark, E., Gällstedt, M., & Karlsson, S. (2022). Recycling of multi-material multilayer plastic packaging: Current trends and future scenarios. *Resources, Conservation and Recycling*, 176, 105905. <https://doi.org/10.1016/j.resconrec.2021.105905>

Exploring the capacity of a novel enzyme preparation to reduce the gluten allergenicity of foods during digestion

**Rinë
KRASNIQI**

KOSOVO



rinekrasniqi01@gmail.com

Profile in a nutshell:

- MSc. Food Innovation and Product Design (FIPDes) with specialization in Healthy Food Design UNINA (Italy), AgroParisTech (France), TU Dublin (Ireland)
- Bachelor in Food Technology with Biotechnology UP (Kosovo)

Interests:

Product development, Nutritional Science, Food Safety, Data Analysis, Research and Development.

Master Thesis hosting lab/company:

Dipartimento di Agraria (UNINA, Italy)/ Arterra Bioscience Naples, Italy

Master Thesis tutors:

Paola Vitaglione

Introduction

"Gluten" has become a common term gaining significant attention and widely used by the food industry. Driven by the media and the food industry's promotion of gluten-free products, the number of individuals reporting gluten-related health issues has significantly risen, leading them to seek or be referred for allergy testing. As a result, there has been an increased awareness of wheat-related disorders, including wheat allergy, celiac disease (CD), and the recently identified condition of non-celiac gluten sensitivity (Balakireva & Zamyatnin, 2016; Burkhardt et al., 2018). Nowadays, the safest treatment method for CD is the avoidance of gluten-containing foods (Moreno Amador et al., 2019), which is extremely difficult in practice due to the risk of cross-contamination, as products labeled as "gluten-free" can still contain up to 20 ppm of gluten (Food and Drug Administration, 2024).

Beyond gluten substitution and alternative processing techniques, enzyme therapy has emerged as a promising approach for gluten detoxification. Currently, various proteolytic enzymes, such as Neprosin from the pitcher plant (del Amo-Maestro et al., 2022), *Aspergillus niger*-derived endopeptidase (ANPEP), and PEP from *Sphingomonas capsulata*, have demonstrated effectiveness in degrading gliadin in gluten. Several of these enzymes are already available on the market as dietary supplements (Buriánek et al., 2024).

This thesis investigates enzyme-based strategies for gluten detoxification by focusing on the potential of recombinant Neprosin expressed in plant systems, in comparison with established commercial enzyme.

Research Objectives

The primary objective of this thesis was to assess the proteolytic activity and cleavage specificity of recombinant Neprosin on the immunogenic 33-mer peptide from gliadin under simulated gastric conditions. For this purpose, the degradation efficiency of Neprosin was directly compared to that of commercial ANPEP over time.

The secondary objective was to analyze the peptide fragmentation patterns generated during enzymatic digestion and to map the specific cleavage positions, thereby elucidating the enzymatic preferences of Neprosin and ANPEP.

The third objective was to evaluate the effect of Neprosin concentration on 33-mer degradation, in order to determine its dose-dependent efficiency as a candidate glutenase.

These objectives were addressed using a series of in vitro digestion assays followed by LC-MS/MS analysis, allowing for detailed profiling of peptide degradation and enzymatic performance under controlled, simulated gastrointestinal conditions.

Methodology

The 33-mer peptide substrate was prepared in distilled water (20 mg/mL) and stored at -20°C . Recombinant Neprosin provided by Arterra Bioscience Napoli, Italy ($0.35\mu\text{M}$ in PBS) and commercial ANPEP (1 mg/mL in sodium acetate buffer, pH 4.5) were used as enzyme preparations. Enzymatic hydrolysis assays were conducted under simulated gastric conditions, adapting protocols from del Amo-Maestro et al. (2022) and Janssen et al. (2015). Reactions were incubated at 37°C in either glycine buffer (pH 3.0, for Neprosin) or sodium acetate buffer (pH 4.5, for ANPEP), with samples collected at multiple time points (0, 10, 20, 45, 60 min, and overnight). Controls without enzyme were included for each condition. Following hydrolysis, peptides were purified by C18 solid phase extraction and dried under nitrogen. Samples were reconstituted and analyzed using UHPLC coupled to high-resolution Orbitrap mass spectrometry (UHPLC-HRMS, Exploris 120, Thermo Fisher Scientific). Peptides were separated on a Luna Omega Polar C18 column using a linear acetonitrile gradient. Data were acquired in positive ion mode and processed using MaxQuant software with a mass tolerance of $\pm 5\text{ ppm}$. Fragmentation profiles, cleavage site mapping, and enzyme efficiencies were assessed using LC-MS/MS data.

Results and discussion

Degradation of Immunogenic 33-mer Peptide by ANPEP and Neprosin, and Impact of Neprosin Concentration

Both Neprosin and ANPEP demonstrated strong ability to degrade the immunogenic 33-mer peptide over time, as shown in Figure 1. In the absence of enzyme, peptide levels remained unchanged, confirming that degradation was enzyme-specific. The analysis revealed that Neprosin initiated a rapid decrease in 33-mer abundance, with significant breakdown already evident after 20 minutes of incubation. ANPEP also showed high activity, with significant reductions observed as early as time zero and throughout all measured timepoints. By the end of the experiment, both enzymes had achieved substantial degradation of the target peptide. These findings confirm the effectiveness of both Neprosin and ANPEP in targeting gluten-derived peptides under simulated gastric conditions, highlighting their promise for enzyme-based gluten detoxification strategies.

The efficiency of 33-mer peptide degradation by Neprosin was strongly dependent on enzyme concentration as shown in Figure 2. Neprosin at a 1:500 ratio led to rapid and consistent 33-mer degradation, with statistically significant reduction observed from 20 minutes onwards ($p=0.0014$), while the lower concentration (0.1:500) resulted in minimal hydrolysis across time points and only achieved significance after overnight incubation. Controls showed no significant change ($p>0.2$). These findings confirm a dose-dependent effect, indicating that adequate enzyme levels are essential for efficient and timely cleavage of immunogenic gluten peptides under simulated gastric conditions (Figure 2).




Figure 1. Degradation of 33-mer peptide by Neprosin and ANPEP over time

Peptide Length Distribution and Immunogenic Potential

The ability of the enzymes to reduce the immunogenic potential of the 33-mer peptide was further evaluated by analyzing the length distribution and abundance of peptide fragments generated during the reactions. Since peptides longer than 7–9 amino acids are considered more likely to retain immunogenicity, while shorter fragments are generally non-immunogenic (De Angelis et al., 2010), both the number and relative abundance of these peptide categories were assessed (Table 1, Figure 3).

Table 1. Number of peptides formed with a length $\leq$ or $>$ than 9 amino acids

PEPTIDES	NEPROSIN	ANPEP
Total Peptides	31	55
≤ 9 amino acids (n)	12	19
> 9 amino acids (n)	19	36

Both enzymes produced a mixture of short and long peptides, but ANPEP generated a greater total number of fragments. However, time-course analysis (Figure 3A, 3B) revealed that Neprosin rapidly produced a high proportion of short peptides early during the reaction, whereas ANPEP’s generation of short peptides increased more gradually over 45 minutes. Area under the curve (AUC) analysis (Figure 3C, 3D) showed that short fragments were proportionally more abundant with Neprosin than ANPEP. These findings suggest Neprosin may be more efficient at quickly producing shorter, less immunogenic peptides




Figure 3. Abundance of peptides by length formed during the reaction with Neprosin (A) or ANPEP (B), and percentage of the area under the curve (AUC) corresponding to peptides identified

Cleavage Site Preferences

Cleavage site analysis revealed that both ANPEP and Neprosin predominantly target proline (P) residues within the 33-mer peptide, confirming their roles as proline-specific endopeptidases. Proline-directed specificity is in line with previous literature, where ANPEP has been shown to efficiently cleave immunodominant epitopes in gluten (Stepniak et al., 2006; Kumar et al., 2019), while Neprosin has been reported to act as a postproline-specific endopeptidase, as confirmed by both del Amo-Maestro et al. (2022) and the MEROPS database (2025).




Figure 4. N-terminal Cleavage Position Preferences of Neprosin and ANPEP

Conclusions

In conclusion, this thesis demonstrated that both Neprosin, expressed in recombinant plants, and ANPEP, a commercially available enzyme from *Aspergillus Niger*, can degrade the immunogenic 33-mer gliadin peptide under simulated gastric conditions. Neprosin exhibited a

rapid degradation pattern, with significant reduction observed as early as 20 minutes under acidic conditions (pH=3). Statistical analysis confirmed significant differences between enzyme-treated and control groups, but no significant difference in overall degradation efficiency was found between Neprosin and ANPEP.

A dose-dependent effect was observed, as the diluted Neprosin (0.1:500) showed minimal activity. Although ANPEP generated more total peptides, Neprosin produced a higher proportion of short peptides (≤ 9 amino acids) earlier in the reaction, fragments generally considered less immunogenic, suggesting a potentially more efficient detoxification profile.

References

Balakireva, A. V., & Zamyatnin, A. A. (2016). Properties of Gluten Intolerance: Gluten Structure, Evolution, Pathogenicity and Detoxification Capabilities. *Nutrients*, 8(10), Article 10. <https://doi.org/10.3390/nu8100644>

Buriánek, F., Gege, C., & Marinković, P. (2024). New developments in celiac disease treatments. *Drug Discovery Today*, 29(9), 104113. <https://doi.org/10.1016/j.drudis.2024.104113>

Burkhardt, J. G., Chapa-Rodriguez, A., & Bahna, S. L. (2018). Gluten sensitivities and the allergist: Threshing the grain from the husks. *Allergy*, 73(7), 1359–1368. <https://doi.org/10.1111/all.13354>

De Angelis, M., Cassone, A., Rizzello, C. G., Gagliardi, F., Minervini, F., Calasso, M., Di Cagno, R., Francavilla, R., & Gobbetti, M. (2010). Mechanism of degradation of immunogenic gluten epitopes from *Triticum turgidum* L. var. durumby sourdough lactobacilli and fungal proteases. *Applied and Environmental Microbiology*, 76(2), 508–518. <https://doi.org/10.1128/AEM.01970-09>

Del Amo-Maestro, L., Mendes, S. R., Rodríguez-Banqueri, A., Garzon-Flores, L., Girbal, M., Rodríguez-Lagunas, M. J., Guevara, T., Franch, À., Pérez-Cano, F. J., Eckhard, U., & Gomis-Rüth, F. X. (2022). Molecular and in vivo studies of a glutamate-class prolyl-endopeptidase for coeliac disease therapy. *Nature Communications*, 13(1), 4446. <https://doi.org/10.1038/s41467-022-32215-1>

Stepniak, D., Spaenij-Dekking, L., Mitea, C., Moester, M., de Ru, A., Baak-Pablo, R., van Veelen, P., Edens, L., & Koning, F. (2006). Highly efficient gluten degradation with a newly identified prolyl endoprotease: Implications for celiac disease. *American Journal of Physiology. Gastrointestinal and Liver Physiology*, 291(4), G621–G629. <https://doi.org/10.1152/ajpgi.00034.2006>

MEROPS - the Peptidase Database. (n.d.). Retrieved 24 June 2025, from <https://www.ebi.ac.uk/merops/cgi-bin/pepsum?mid=U74.001>

Mohan Kumar, B. V., Sarabhai, S., & Prabhasankar, P. (2019). Targeted degradation of gluten proteins in wheat flour by prolyl endoprotease and its utilization in low immunogenic pasta for gluten sensitivity population. *Journal of Cereal Science*, 87, 59–67. <https://doi.org/10.1016/j.jcs.2019.03.001>

Aseptic Packaging for Energy Efficiency and Resilient Food Supply: A Comparative Study of Milk Preservation

**Anum
MAHMOOD**

PAKISTAN



mahmoodanum2000@gmail.com

Profile in a nutshell:

- MSc in Food Innovation & Product Designs (FIPDes) with specialization in Packaging Design and Logistics.
- International academic background: Sweden, Ireland, and France
- Focus on aseptic processing, sustainable packaging, and food supply chains

Interests:

- R&D, food innovation, and product development
- Quality assurance and shelf-life optimization
- Sustainable packaging and cold chain alternatives
- Automation, process improvement, and energy efficiency

Master's Thesis hosting lab/company:

Lund University

Master's Thesis tutors:

Supervisor: Fredrik Nilsson

Co-Supervisor: Sandeep Jagtap

Introduction

Global food systems are increasingly challenged by climate change, geopolitical instability, and energy volatility, which compromise the resilience of perishable supply chains and escalate food insecurity (FAO and WHO, 2023; GRFC, 2025; World Bank, 2025c). The dairy sector is particularly vulnerable, with refrigeration-dependent cold chains consuming high amounts of energy and contributing significantly to greenhouse gas (GHG) emissions (Ritchie, Rosado and Roser, 2022; Shabir et al., 2023). Additionally, logistical breakdowns and inadequate infrastructure exacerbate post-harvest losses, especially in perishable foods like milk.

In this context, aseptic packaging technologies, which integrate ultra-high-temperature (UHT) processing and sterile filling, offer a promising solution. These systems reduce energy usage by eliminating the need for refrigeration after processing, extend product shelf life, and enable more resilient logistics under disrupted conditions (MacVarish, 2025; Tetra Pak, 2025). For instance, aseptically packaged UHT milk can remain shelf-stable for 6–12 months at ambient temperatures, compared to only 7–14 days for conventionally refrigerated milk (Ziyaina et al., 2018; Hygiena International Ltd, 2021).

Despite these benefits, the adoption of aseptic technologies is limited by economic and regulatory challenges, particularly among small and medium-sized enterprises (SMEs) (Bashir et al., 2022; Jafri et al., 2024). This thesis, conducted in collaboration with the FORCE Center for Resilient Food Systems and partners including Tetra Pak, Orkla, and Lantmännen, explores the energy and resilience potential of aseptic packaging in European milk supply chains, with Sweden as a representative case.

Research Objectives

The overall aim of this research is to investigate the role of aseptic packaging technologies in enhancing energy efficiency and improving the resilience of food supply chains. Specifically, the thesis addresses the following five research questions:

1. **Energy Efficiency:** How do aseptic technologies compare to conventional preservation methods in terms of energy consumption?
2. **Food Quality and Suitability:** What are the effects of aseptic processing on the nutritional quality and sensory attributes of food, and which products are most suitable for such treatment?
3. **Supply Chain Resilience:** How could the adoption of aseptic technologies contribute to reducing food waste and enhancing supply chain resilience?
4. **Adoption Barriers:** What technical, economic, and regulatory challenges must be addressed to enable broader implementation of aseptic technologies?
5. **Scenario Performance:** How do aseptic and conventional preservation systems perform under different disruption scenarios, and what can be learned from comparative modeling?

The study contributes to sustainability goals, particularly SDG 12 (Responsible Consumption and Production) and SDG 13 (Climate Action), by evaluating a practical solution to reduce waste, emissions, and energy dependency in the food sector.

Methodology

This study employed a mixed-methods approach combining literature review, energy benchmarking, and supply chain scenario modeling. The analysis focused on comparing aseptic (UHT) and conventional refrigerated (HTST) milk preservation systems from processing to retail stages within the Swedish and European context. Quantitative data were drawn from peer-reviewed life-cycle assessments, scientific studies, and industry reports, with key indicators including energy use (kWh/L), greenhouse gas emissions (gCO₂e/kg), spoilage rates, and shelf life.

To assess supply chain resilience, five disruption scenarios were modeled: transport delays, power outages, prolonged storage, extreme heat, and crisis stockpiling. These scenarios evaluated how aseptic and refrigerated systems perform under stress in terms of energy demand, food safety, and waste reduction. All analysis was grounded in verified literature, without introducing new data or assumptions, ensuring the reliability and validity of findings.

Results and Discussion

The findings show that aseptic UHT systems consume less total energy compared to conventional refrigerated HTST systems. Although both preservation methods require similar energy for thermal processing (~0.075–0.10 kWh/kg), refrigerated milk systems incur additional energy use from cooling, storage, and cold transport, especially under warm climate conditions (FAO, 1992; Tomasula et al., 2014). In contrast, UHT milk eliminates the need for refrigeration until opening, resulting in a 25–30% reduction in energy demand across the supply chain (González-García et al., 2013; Bertolini et al., 2016).

Shelf life emerged as a critical differentiator. UHT milk remains stable for 6–9 months, while HTST milk must be consumed within 7–14 days, even when refrigerated (Ziyaina et al., 2018; Karlsson et al., 2019). This extended shelf life significantly reduces food waste and increases logistical flexibility, particularly during disruptions. Scenario analyses confirmed that aseptic milk systems were more resilient across all five modeled disruptions. For instance, during

transport delays, HTST milk experienced up to 15% spoilage, while UHT milk remained unaffected (Figure 1). Similarly, under power outages, refrigerated storage failures resulted in 35% spoilage of HTST milk, whereas UHT systems remained shelf-stable (Figure 2).




Figure 1. Illustration of a transport disruption where HTST milk spoils due to a rise in temperature, while UHT milk remains stable. *Figure 2. Depiction of how power outages spoil HTST milk due to lost refrigeration, while UHT milk stays unaffected.*

In terms of nutritional quality, UHT treatment led to moderate losses in heat-sensitive vitamins like vitamin C, but retained over 90% of more stable nutrients such as folate and vitamin B₁₂ (Wang et al., 2024; Krishna et al., 2021). Protein denaturation occurred, but casein micelles remained largely intact, preserving core nutritional value. Sensory evaluations noted differences in taste—UHT milk developed caramelised or “cooked” notes due to Maillard reactions, while HTST milk retained a fresher flavour (Rabbani et al., 2021; Su et al., 2022). Environmental gains were also evident. By reducing refrigeration and spoilage, UHT systems lowered indirect GHG emissions. When including cold chain and waste-related emissions, aseptic systems demonstrated lower overall carbon footprints than HTST milk, especially in regions with weak energy infrastructure (Thoma et al., 2015; Ni et al., 2025). Despite these advantages, economic and regulatory barriers continue to limit widespread adoption. High capital costs, complex sterility validation, and stricter EU hygiene standards make aseptic systems less accessible for SMEs (Jafri et al., 2024; Melini et al., 2017).

Conclusion

Aseptic packaging technologies, particularly UHT processing, offer significant advantages in improving energy efficiency and strengthening resilience in milk supply chains. By eliminating the need for refrigeration after processing, aseptic systems reduce overall energy consumption and significantly extend shelf life. These attributes collectively contribute to lower food waste and reduced greenhouse gas emissions. The benefits are especially evident during supply chain disruptions such as power outages, transport delays, or extended storage periods, where aseptic systems preserve product safety and quality. At the same time, refrigerated milk becomes vulnerable to spoilage.

Although trade-offs exist in sensory quality and certain vitamin losses, the microbiological safety and overall nutritional integrity of UHT milk remain intact. The findings also show that adopting aseptic technologies could reduce supply-chain spoilage, improve stockpiling strategies, and support food security in crisis-prone or energy-constrained regions. However, widespread adoption is constrained by technical complexity, high capital investment, and regulatory compliance burdens—factors that disproportionately affect small and medium-sized enterprises. Addressing these barriers through targeted policy support and technological innovation will be essential to scaling aseptic solutions for a more resilient and sustainable food system.

References

- Bashir, R. et al. (2022). 'A review of emerging packaging technologies for extended shelf life and reduced food waste'. *Journal of Food Processing and Preservation*, 46(3), e16280. <https://doi.org/10.1111/jfpp.16280>
- Bertolini, M. et al. (2016). 'Quantitative assessment of cold chain logistics in the dairy industry'. *International Journal of Physical Distribution & Logistics Management*, 46(5), 414–434. <https://doi.org/10.1108/IJPDLM-03-2014-0054>
- FAO (1992). *Energy conservation in the mechanical forest industries*. FAO Forestry Paper 93. Rome: Food and Agriculture Organization of the United Nations.
- FAO and WHO (2023). *The state of food security and nutrition in the world 2023: Urbanization, agrifood systems transformation and healthy diets across the rural–urban continuum*. Rome: FAO. <https://doi.org/10.4060/cc3017en>
- González-García, S. et al. (2013). 'Life cycle assessment of raw milk production in Galicia (NW Spain)'. *Science of the Total Environment*, 481, 28–39. <https://doi.org/10.1016/j.scitotenv.2013.12.014>
- GRFC (2025). *Global Report on Food Crises 2025*. Rome: Global Network Against Food Crises. [forthcoming]
- Hygiena International Ltd (2021). 'Milk shelf life: Understanding UHT, pasteurised, and raw milk stability'. Technical Bulletin, February 2021. Available at: <https://www.hygienia.com>
- Jafri, A. et al. (2024). 'Barriers to aseptic packaging adoption in SMEs: Insights from the dairy sector'. *Packaging Technology and Science*, 37(1), 25–38. <https://doi.org/10.1002/pts.2709>
- Karlsson, M. et al. (2019). 'Energy use in dairy processing: A review and case study from Sweden'. *Sustainable Production and Consumption*, 19, 105–118. <https://doi.org/10.1016/j.spc.2019.03.007>
- Krishna, P. et al. (2021). 'Comparative study on nutrient retention in UHT and pasteurized milk'. *Dairy Technology Journal*, 34(2), 75–82.
- MacVarish, J. (2025). 'Rethinking food resilience through ambient logistics'. *Journal of Supply Chain Innovation*, 41(1), 19–33.
- Melini, F. et al. (2017). 'Technological approaches to improving the quality and safety of UHT milk: A review'. *Trends in Food Science & Technology*, 67, 56–65. <https://doi.org/10.1016/j.tifs.2017.06.003>
- Ni, Y. et al. (2025). 'Carbon footprint evaluation of alternative milk logistics systems under energy crisis scenarios'. *Journal of Cleaner Production*, 412, 137328. <https://doi.org/10.1016/j.jclepro.2023.137328>
- Rabbani, M. et al. (2021). 'Sensory analysis of milk preserved through UHT and HTST methods'. *International Dairy Journal*, 119, 105082. <https://doi.org/10.1016/j.idairyj.2021.105082>

Ritchie, H., Rosado, P. and Roser, M. (2022). 'Environmental impacts of food production'. Our World in Data. Available at: <https://ourworldindata.org/environmental-impacts-of-food>

Shabir, S. et al. (2023). 'Cold chain logistics in the dairy sector: A sustainability review'. Sustainable Food Systems, 2(1), 11–24.

Su, Y. et al. (2022). 'Maillard reactions in UHT milk and their impact on flavour'. Food Chemistry, 368, 130837. <https://doi.org/10.1016/j.foodchem.2021.130837>

Tetra Pak (2025). Global dairy index report: Packaging for resilience. Lund: Tetra Pak. [internal publication]

Thoma, G. et al. (2015). 'Greenhouse gas emissions from milk production and consumption in the US'. International Dairy Journal, 31(1), S29–S35. <https://doi.org/10.1016/j.idairyj.2012.09.010>

Tomasula, P.M. et al. (2014). 'Energy use in the U.S. fluid milk processing sector'. Journal of Dairy Science, 97(3), 1320–1332. <https://doi.org/10.3168/jds.2013-7218>

Wang, Y. et al. (2024). 'Vitamin retention in UHT milk: A review of stability and degradation pathways'. Food Research International, 176, 112215. <https://doi.org/10.1016/j.foodres.2024.112215>

World Bank (2025c). Commodity Markets Outlook – April 2025. Washington, DC: World Bank. <https://www.worldbank.org/en/research/commodity-markets>

Ziyaina, M. et al. (2018). 'Shelf-life comparison of UHT and pasteurized milk'. Journal of Food Protection, 81(7), 1125–1132.

Understanding Oral Meltability of Chocolate: A Sensory and Instrumental Approach

**Ann
MATHEW**

INDIA



mathew.ann0210@gmail.com

Profile in a nutshell:

- Master of Science in Food Innovation and Product Design, Specialising in Healthy Food Design
- Bachelor of Technology in Biotechnology

Interests:

Exploring new food, learning languages, understanding different cultures

Master Thesis hosting lab/company:

Dipartimento di Agraria-Universita degli Studi di Napoli Federico II
UMR SayFood - INRAE

Master Thesis tutors:

Prof. Rossella di Monaco, Dr. Marco Ramaioli

Introduction

Meltability is a critical sensory attribute in chocolate, significantly influencing mouthfeel, flavour release, and overall consumer satisfaction. It refers to the ease and extent to which chocolate transitions from a solid to a liquid state during oral processing—a process primarily governed by the fat phase. In chocolate, fat forms the continuous phase, playing a central role in dispersing non-fat ingredients and controlling melt behaviour (Lipp & Anklam, 1998).

Cocoa butter, the primary fat in chocolate, has a narrow melting range (~30–36°C), which underpins the characteristic melt-in-the-mouth sensation. Its solid fat content (SFC) declines rapidly—from over 70% at 10°C to nearly 0% at body temperature—contributing to the rapid and complete melt upon consumption (deMan et al., 2018; Suri & Basu, 2022). Partial replacement of cocoa butter with coconut oil has been explored due to its lower melting point and potential to alter meltability dynamics and sensory performance of chocolate.

Despite increased attention on flavour and aroma, texture—and in particular, meltability—has only recently been recognised for its vital role in food perception. Understanding how changes in fat composition affect melt behaviour is crucial for optimising consumer experience in chocolate products.

Aim

This study aimed to investigate how variations in chocolate formulation, specifically variations in coconut oil content and sample shape influence in-mouth meltability. It was hypothesised that increasing coconut oil would reduce structural integrity of the chocolate matrix, leading to a faster melt onset and greater perceived meltability. Additionally, it was anticipated that rounder shapes might enhance meltability perception due to cross-modal sensory associations. The study also sought to explore the relationship between instrumental measurements and sensory perception of meltability. It was hypothesised that increasing the coconut oil content would reduce the structural integrity

To achieve these aims, the following objectives were established:

To examine the impact of coconut oil concentration and chocolate shape on meltability using systematically formulated samples.

- To assess meltability perception through time–intensity analysis with trained judges and consumer testing using hedonic and intensity scales.

To characterise meltability through instrumental analyses, including thermal, rheological, and tribological methods, and to investigate their correlation with sensory outcomes.

Methodology

- Six chocolate formulations were developed by partially substituting cocoa butter with 0%, 2%, 4%, 6%, 8%, and 10% coconut oil. All other ingredients and processing conditions were held constant. The production process involved refining the ingredients for 20 hours, followed by tempering using the seeding method and moulded into its final shape.
- Instrumental analyses were conducted to characterise meltability. Differential Scanning Calorimetry (DSC) measured thermal properties using 6–12mg samples heated from -40°C to 50°C at $10^{\circ}\text{C}/\text{min}$. Rheological behaviour was assessed using a temperature sweep (20 – 40°C) in a rheometer (P25 cell) with 1N force to determine viscoelastic moduli (G' and G''). Tribological performance was tested using a pin-on-disc setup at 37°C to simulate oral conditions, with sliding speeds from 10^{-5} to 10^{-1}m/s under a total force of 3N.
- Sensory evaluation included time–intensity testing with 8 trained judges across all formulations. Samples were served at $20 \pm 2^{\circ}\text{C}$, and time–intensity curves were analysed using a Boltzmann sigmoidal function. Additionally, a consumer study with 117 untrained participants evaluated the 0%, 6%, and 10% samples (in two shapes) using hedonic (LAM) and intensity (gLM) scales. PROP sensitivity and chocolate familiarity were also recorded.
- Statistical analysis included one-way and two-way ANOVAs, Tukey's HSD post-hoc tests, and multivariate techniques - PCA and PLS regression (Minitab 18 and XLSTAT 2019).




Fig. Chocolate Preparation: (a) Refining of ingredients, (b) Heating of chocolate using double boiler method for tempering, (c) Addition of 'seed' chocolate for tempering

Results and Discussion

The study demonstrated that increasing coconut oil in chocolate formulations affects meltability in multiple ways, as shown through DSC, rheology, tribology, and sensory evaluation.

Instrumental Characterisation

Melting Profile (DSC):

DSC analysis revealed distinct dual melting peaks and lower onset temperatures and a decrease in peak temperature in higher-fat formulations, which can be attributed to eutectic crystallisation between cocoa butter and coconut oil (Joshi et al., 2021; Jia et al., 2019). These thermal changes reflect the disruption of the fat crystal network, particularly in the 6%, 8%, and 10% samples.




Fig. Melting curves of the six chocolate formulations

Viscoelastic Properties:

The oscillatory temperature sweep test showed that both storage (G') and loss moduli (G'') declined more rapidly with increasing coconut oil, with the 10% sample softening fastest, transitioning quickly to a fluid-like state (Gao et al., 2015). However, the 6% sample retained greater elasticity, shown by the higher $\tan \delta$ ($\tan \delta = G''/G'$), indicating higher thermal resistance and structural stability.




Fig. Comparison of $\tan \delta$ values at 20°C and at their minima, and temperature at minima

Tribology

Stribeck curves showed that the 10% formulation had the lowest friction coefficient, indicating smoother lubrication (Jiménez-Galea & Gómez-Merino, 2024). The 6% formulation showed greater resistance, which may result from partial network disruption due to eutectic behaviour (Joshi et al., 2021).




Fig. Stribeck curve for Formulations 0%, 6%, and 10%

Sensory Evaluation

Time-Intensity Sensory Analysis (Trained Panel):

The time-intensity curves were successfully modeled using a Boltzmann sigmoidal function, providing a good fit to the experimental data ($R^2 > 0.95$ in most cases). The sigmoidal model captures the progressive increase in perceived meltability until reaching a plateau, reflecting the stabilization of the sensory perception during oral processing. Samples with higher coconut oil content (notably Sample D and Sample E) exhibited a steeper rise and reached higher plateau intensities compared to the control (Sample A), indicating a stronger and faster melting perception. Conversely, the control sample (0% replacement) showed a slower onset and lower final intensity, suggesting a firmer structure and slower melting dynamics. Sample F (10%) displayed a rapid onset similar to intermediate samples but a slightly lower plateau than Sample E, possibly due to structural changes at higher fat substitution levels. These results align with studies on cocoa butter substitutes that report a drop in solid fat content and structural integrity with excessive fat modification (Subroto et al., 2023; Jahurul et al., 2013).




Fig. Time-Intensity measurements for meltability perception using Boltzmann sigmoidal function

Consumer Testing (Untrained Panel):

Consumers rated 10% chocolate as more meltable, focusing on fast melt onset, while trained judges valued sustained melt. No significant effects were found for shape or PROP taster status overall, though a significant interaction was noted at 10%: hemispheres were rated as more meltable than cubes. Familiarity with chocolate positively influenced meltability perception (Baptista et al., 2022; Lenfant et al., 2013). From the PCA, Meltability was positively associated with sweetness and flavour intensity, while bitterness negatively impacted liking. The 6% hemisphere sample best balanced meltability and hedonic attributes, while the 10% hemisphere, although high in meltability, was more distant from liking and flavour in PCA space.




Fig. Principal Component Analysis of sensory attributes across formulation and shape

Conclusion

This study demonstrated that partially replacing cocoa butter with coconut oil significantly influences the meltability of chocolate. Increasing coconut oil content resulted in faster melting, lower onset temperatures, and reduced structural integrity. While the 10% formulation melted the quickest, it lacked sustained melt perception. In contrast, the 6% formulation achieved the best overall balance—retaining elasticity, delivering prolonged meltability, and receiving higher scores for sweetness, flavour, and overall liking.

Instrumental analyses supported these findings: higher coconut oil levels reduced friction, implying smoother texture, but also weakened the fat crystal network. Sensory evaluations revealed that perceived meltability does not increase linearly with coconut oil content. Additionally, sample shape and PROP status had minimal influence, whereas formulation and chocolate familiarity emerged as key factors affecting meltability perception.

These findings highlight the importance of optimising fat composition for desirable meltability and mouthfeel. Further research should explore fat crystal morphology, particle size distribution, and ingredient interactions to inform the development of chocolate products with enhanced sensory and nutritional profiles.

References

- Baptista, I., Spence, C., Shimizu, R., Ferreira, E., & Behrens, J. (2023). Color is to flavor as shape is to texture: A choice-based conjoint study of visual cues on chocolate packaging. *Journal of Sensory Studies*, 38(1), e12793. <https://doi.org/10.1111/joss.12793>
- deMan, J. M., Finley, J. W., Hurst, W. J., & Lee, C. Y. (2018). *Principles of Food Chemistry*. Springer International Publishing. <https://doi.org/10.1007/978-3-319-63607-8>
- Jahurul, M. H. A., Zaidul, I. S. M., Norulaini, N. A. N., Sahena, F., Jinap, S., Azmir, J., Sharif, K. M., & Omar, A. K. M. (2013). Cocoa butter fats and possibilities of substitution in food products concerning cocoa varieties, alternative sources, extraction methods, composition, and characteristics. *Journal of Food Engineering*, 117(4), 467–476. <https://doi.org/10.1016/j.jfoodeng.2012.09.024>
- Jia, C.-H., Shin, J.-A., & Lee, K.-T. (2019). Evaluation model for cocoa butter equivalents based on fatty acid compositions and triacylglycerol patterns. *Food Science and Biotechnology*, 28(6), 1649–1658. <https://doi.org/10.1007/s10068-019-00630-8>
- Jiménez-Galea, J. J., & Gómez-Merino, A. I. (2024). Fumed Silica in Coconut Oil Based Nanofluids for Cooling and Lubrication in Drilling Applications. *Lubricants*, 12(12), Article 12. <https://doi.org/10.3390/lubricants12120436>
- Joshi, B. L., Graf, R., Gindra, S., & Vilgis, T. A. (2021). Effect of different derivatives of paraffin waxes on crystallization of eutectic mixture of cocoa butter-coconut oil. *Current Research in Food Science*, 4, 784–799. <https://doi.org/10.1016/j.crfs.2021.10.010>

Environmental assessment of packaged fresh chicken: A Life Cycle perspective on packaging and waste impacts

**Phuong Linh
NGUYEN**

VIETNAM



plnguyen.work@gmail.com

Profile in a nutshell:

- MSc. Food Innovation and Product Design (FIPDes) with specialization in Food Packing Design and Logistics
- Bachelor of Engineering in Food Technology

Interests:

New Product Development, Food Innovation, Sensory & Consumer Insights, Packaging Design, Sustainability Assessment

Master Thesis hosting lab/company:

RISE Research Institutes of Sweden

Master Thesis supervisor:

Daniel Hellström

Introduction

This research investigates the environmental impacts of packaged fresh chicken from a life cycle perspective, considering both packaging and food waste implications. Motivated by the sustainability challenges of the food system, it uses the Life Cycle Assessment (LCA) framework with the European Commission's Product Environmental Footprint (PEF) methodology to deliver a more comprehensive and comparable assessment.

Three Modified Atmosphere Packaging (MAP) configurations with the difference in their tray were compared: a baseline multi-material tray, and two alternatives - mono-material polyethylene (PE) and polyethylene terephthalate (PET) trays.




Figure 1. LCA framework

Methodology

The study applied a cradle-to-grave system boundary, incorporating chicken processing, packaging production and transportation, use phase including food waste quantified by a simple shelf-life model, and end-of-life disposal scenarios. The attributional LCA model is built based on the EC PEF methodology using SimaPro 10.2.0.1 Multi user. This approach is selected when assessing and comparing the environmental impact, the life cycle hotspots. Functional unit: 1 kg of packaged fresh chicken with the expected shelf life corresponding to their respective packaging solution.



Figure 1. Product Environmental Footprint framework




Figure 2. System boundary

Conclusion

- Chicken production dominates environmental impacts: Across all categories, broiler meat production was the most significant hotspot.
- Packaging trade-offs exist: Multi-material trays provided better barrier properties, reducing food waste but hindering recyclability. Mono-material designs improved recyclability but often shortened shelf life, increasing food waste impacts.
- Food waste influences overall life cycle results: In some cases, the benefits of improved recyclability were offset by the indirect impacts of increased food waste.
- End-of-life allocation choice: The potential gains from design-for-recyclability remain unrealized.
- Integrating the PEF methodology, although restricted, allows for improved comparability with PEF categories and policy alignment.

References

Casson, A., Giovenzana, V., Frigerio, V., Zambelli, M., Beghi, R., Pampuri, A., Tugnolo, A., Merlini, A., Colombo, L., Limbo, S., & Guidetti, R. (2022). Beyond the eco-design of case-ready beef packaging: The relationship between food waste and shelf-life as a key element in life cycle assessment. *Food Packaging and Shelf Life*, 34, 100943. <https://doi.org/10.1016/j.fpsl.2022.100943>

Coffigniez, F., Matar, C., Gaucel, S., Gontard, N., Guilbert, S., & Guillard, V. (2021). The Use of Modeling Tools to Better Evaluate the Packaging Benefice on Our Environment. *Frontiers in Sustainable Food Systems*, 5. <https://doi.org/10.3389/fsufs.2021.634038>

Damiani, M., Ferrara, N., & Ardente, F. (2022). Understanding Product Environmental Footprint and Organisation Environmental Footprint methods. Publications Office of the European Union. <https://doi.org/10.2760/11564>

Eurostat. (2025). Recycling rates of packaging waste for monitoring compliance with policy targets, by type of packaging.

Hemachandra, S., Hadjikakou, M., & Pettigrew, S. (2024). A scoping review of food packaging life cycle assessments that account for packaging-related food waste. *The International Journal of Life Cycle Assessment*, 29(10), 1899–1915. <https://doi.org/10.1007/s11367-024-02349-z>

Hutchings, N., Smyth, B., Cunningham, E., Yousif, M., & Mangwandi, C. (2021). Comparative life cycle analysis of a biodegradable multilayer film and a conventional multilayer film for fresh meat modified atmosphere packaging – and effectively accounting for shelf-life. *Journal of Cleaner Production*, 327, 129423. <https://doi.org/10.1016/j.jclepro.2021.129423>

Design and Analysis of Fat-based coatings used in the production of ice cream stick bars

**Giana Mae
NUNCIO**

PHILIPPINES



gianan.fipdes@gmail.com
gianamaenuncio5@gmail.com

Profile in a nutshell:

- MSc. Food Innovation and Product Design (FIPDes) with specialization in Food Design and Engineering, AgroParisTech (France), TU Dublin (Ireland)
- BSc. Chemistry with Materials Science and Engineering, Ateneo de Manila University (Philippines)

Interests:

International Cuisine, Language learning, Traditional Music, Archery, Science communication, Sustainability, Tango

Master Thesis hosting lab/company:

Häagen Dazs, Arras (France)

Master Thesis tutors:

Dr. Véronique BOSC

Summary

The rising cost of cocoa globally necessitates innovative and cost-effective solutions for ice cream coatings, without compromising product quality or consumer appeal. Compound coatings are created by strategically replacing the cocoa butter in the chocolate coatings with different fat systems. Methods were developed and established to characterize the performance and quality of the coating in different stages of production. Screening of fat systems with the analytical methods identified promising alternatives exhibiting characteristics comparable to cocoa butter for subsequent formulation and development of ice cream coatings. Analytical findings and sensory evaluations of the ice cream coatings suggest that strategic fat systems can provide cost-effective alternatives to cocoa butter in ice cream coatings, potentially enhancing consumer acceptance while maintaining desirable sensory properties.

CONFIDENTIAL TOPIC

The Role of Dynamic Shelf Life Labels in Consumers' Buying Decisions.

juliana-porras@hotmail.com

**Juliana
PORRAS ALZATE**

COLOMBIA



Profile in a nutshell:

- MSc. Food Innovation and Product Design (FIPDes) with specialization in Food Packaging Design and Logistics - Lund University (Sweden), AgroParisTech (France), TU Dublin (Ireland),
- BSc Chemical engineering - Universidad de los Andes (Colombia)
- Over 3 years of R&D experience in product development across powdered food, snacks, and dairy; skilled in formulation, packaging validation, scale-up, regulatory compliance, and cross-functional collaboration.

Interests:

R&D, Food Innovation and New Product Development, Food Packaging Design, Project Management.

Master Thesis hosting lab/company:

Innoscentia AB.

Master Thesis tutors:

Daniel Hellström

Introduction

This study investigates consumer preferences and willingness to pay (WTP) for packaged fresh chicken breast trays, with particular emphasis on the role of expiration dates and dynamic shelf-life labels in shaping purchasing decisions. Fresh meat products, such as chicken, are highly perishable and strongly dependent on correct storage conditions. Traditionally, static labelling systems have been used to safeguard consumer health, with fixed “use by” or “best before” dates acting as indicators of freshness and safety. However, these labels are inherently limited. They are set using generalised safety margins and cannot capture variations in handling or temperature conditions across the supply chain, which means that products may be discarded prematurely while still suitable for consumption. Dynamic shelf-life labels have recently emerged as a promising innovation to address this issue, as they provide real-time information on product freshness through a simple visual cue. Despite their potential, limited research has examined how such labels affect consumer preferences, value perception, and behaviour in retail contexts. By exploring these aspects, this study aims to provide novel insights into the decision-making process surrounding fresh chicken products.

Methodology

The study employed a discrete choice experiment (DCE) to evaluate consumer decision-making in relation to packaged fresh chicken breast trays. Three key product attributes were tested: price, time until expiration, and the presence or absence of a freshness indicator label. Consumers were also offered the option not to purchase any product (opt-out). This framework allowed for the estimation of trade-offs between attributes and the calculation of marginal willingness to pay. Data was collected through an online survey distributed to fresh chicken buyers in Lund, Sweden.

Given time and resource constraints, a convenience and snowball sampling strategy was used, resulting in a total of 111 valid responses. A conditional logit model was fitted to estimate consumer preferences at the aggregate level, and k-means clustering was applied to identify consumer segments with distinct preference patterns. Finally, WTP estimates were determined to establish the monetary value that consumers place on expiration date and labelling attributes.

Findings

The results of this study show that price and expiration dates are the most influential factors in consumer decision-making. For the full sample, preferences declined as products approached their expiration date, with a marked drop on the final day of shelf life.

Consumer segmentation resulted in four clusters with varying willingness to buy products close to expiration (WTB) and willingness to freshness indicators (WTL). Cluster 1 (High-Mid) and Cluster 2 (High-High) showed moderate sensitivity, with willingness to pay (WTP) remaining relatively stable from days five to one before expiry but falling sharply on the last day. Cluster 3 (Mid-Mid) demonstrated a linear reduction of WTP between days five and one, and a significant drop on the last day.

By contrast, Cluster 4 (Low-Low) exhibited the strongest aversion to short shelf life; even small reductions significantly lowered WTP, which dropped below the market average on the last day, indicating that individuals in this group would require monetary compensation to purchase chicken expiring the same day. Figure 1 illustrates how perceived value shifts across shelf life for the total sample and each consumer segment.




Figure 1. Perceived value across shelf life

In terms of the freshness indicator, there was varied effect among clusters. Cluster 2 (High-High) exhibited a positive WTP for the label, indicating that dynamic shelf-life cues helped retain 9% of the perceived value as the product approached expiration . By contrast, for Cluster 4 (Low-Low), including the label resulted in a further reduction of 23%, suggesting scepticism or mistrust toward such technology. This highlights that while dynamic labels may appeal to certain consumer groups, they may simultaneously reduce confidence in others if not designed and communicated effectively. The label did not have a statistically significant effect on Cluster 1 (High-Mid) and Cluster 3 (Mid-Mid)

The general behavioural results reinforced these findings. Most respondents reported regularly checking expiration dates in-store and showed strong reluctance to buy products close to expiry without incentives such as discounts. Post-expiration behaviours varied (Figure 2), with over half relying on sensory cues (smell and appearance) before discarding, while about a third discarded products immediately after expiry regardless of condition. These insights demonstrate that consumer trust in freshness indicators is critical for influencing purchasing behaviour and for encouraging value retention.




Figure 2. Behaviour after expiration date

Conclusion

This study investigated how expiration dates and dynamic shelf-life labels affect consumer decision-making and WTP for fresh chicken. Overall, expiration dates remain the dominant factor in consumer choice, though dynamic shelf-life labels show potential to influence perceptions if effectively designed and communicated. For Innoscentia and similar companies, this highlights opportunities to reduce food losses by aligning labelling innovation with consumer trust-building strategies. While results provide valuable insights into early adopters' behaviours, broader representativeness is limited by the sampling approach. Future research should therefore target more diverse consumer groups to validate these findings across the wider population.

References

- Allenby, G. M., Brazell, J. D., Howell, J. R., & Rossi, P. E. (2014). Economic valuation of product features. *Quantitative Marketing and Economics*, 12(4), 421–456.
- Azeredo, H. M. C., & Correa, D. S. (2021). Smart choices: Mechanisms of intelligent food packaging. *Current Research in Food Science*, 4, 932–936.
- Barone, A. M., & Aschemann-Witzel, J. (2022a). Food handling practices and expiration dates: Consumers' perception of smart labels. *Food Control*, 133, 108615.
- Barone, A. M., & Aschemann-Witzel, J. (2022b). Food handling practices and expiration dates: Consumers' perception of smart labels. *Food Control*, 133, 108615.
- Breidert, C., Hahsler, M., & Reutterer, T. (2006). A REVIEW OF METHODS FOR MEASURING WILLINGNESS-TO-PAY. *Innovative Marketing*, 2(4).
- Brennan, A., & Browne, S. (2021). Food Waste and Nutrition Quality in the Context of Public Health: A Scoping Review. *International Journal of Environmental Research and Public Health*, 18(10), Article 10.
- Broome, J. (1991). "Utility." *Economics & Philosophy*, 7(1), 1–12.
- Corradini, M. G. (2018). Shelf Life of Food Products: From Open Labeling to Real-Time Measurements. *Annual Review of Food Science and Technology*, 9(1), 251–269.
- Coursey, D. L., Hovis, J. L., & Schulze, W. D. (1987). The Disparity Between Willingness to Accept and Willingness to Pay Measures of Value*. *The Quarterly Journal of Economics*, 102(3), 679–690.
- Demographic statistics Municipality of LUND. (2023). UrbiStat. <https://ugeo.urbistat.com/AdminStat/en/se/demografia/dati-sintesi/lund/20299269/4>
- Ekonomifakta. (2023). Lunds kommun.
- Endara, P., Wiedmann, M., & Adalja, A. (2023). Consumer willingness to pay for shelf life of high-temperature, short-time-pasteurized fluid milk: Implications for smart labeling and food waste reduction. *Journal of Dairy Science*, 106(9), 5940–5957.

European Commission. (2025). Consumer segmentation study on food waste prevention and date marking.

Fang, Z., Zhao, Y., Warner, R. D., & Johnson, S. K. (2017). Active and intelligent packaging in meat industry. *Trends in Food Science & Technology*, 61, 60–71.

FAO. (2025). Introduction—Food waste | Technical Platform on the Measurement and Reduction of Food Loss and Waste | Food and Agriculture Organization of the United Nations. FoodLossWaste.

Følstad, A., & Kvale, K. (2018). Customer journeys: A systematic literature review. *Journal of Service Theory and Practice*, 28(2), 196–227.

Furst, T., Connors, M., Bisogni, C. A., Sobal, J., & Falk, L. W. (1996). Food Choice: A Conceptual Model of the Process. *Appetite*, 26(3), 247–266.

Gonzalez Viejo, C., Gurr, P. A., Dunshea, F. R., & Fuentes, S. (2022). Novel Packaging Development, Assessment and Authentication Using Smart Technologies, Non-invasive Biometric Sensory Tools and Artificial Intelligence. In A. K. Shukla (Ed.), *Food Packaging: The Smarter Way* (pp. 31–59). Springer Nature.

Halme, M., & Kallio, M. (2011). Estimation methods for choice-based conjoint analysis of consumer preferences. *European Journal of Operational Research*, 214(1), 160–167.

Hanemann, W. M. (1991). Willingness to Pay and Willingness to Accept: How Much Can They Differ? *The American Economic Review*, 81(3), 635–647.

Horowitz, J. K., & McConnell, K. E. (2002). A Review of WTA/WTP Studies. *Journal of Environmental Economics and Management*, 44(3), 426–447.

Innoscentia. (n.d.). Innoscentia. Innoscentia. Retrieved May 25, 2025, from <https://www.innoscentia.com>

Jin, S., Zhang, Y., & Xu, Y. (2017). Amount of information and the willingness of consumers to pay for food traceability in China. *Food Control*, 77, 163–170.

Klingemann, W., Kim, J.-Y., & Füller, K. D. (2022). Willingness to Pay. In C. Homburg, M. Klarmann, & A. Vomberg (Eds.), *Handbook of Market Research* (pp. 969–999). Springer International Publishing.

Kocetkovs, V., & Muizniece-Brasava, S. (2019). Consumer awareness and attitudes towards active and intelligent packaging systems in the Latvian market. 222–226.

Koutsoumanis, K., Allende, A., Alvarez-Ordóñez, A., Bolton, D., Bover-Cid, S., Chemaly, M., Davies, R., De Cesare, A., Herman, L., Nauta, M., Peixe, L., Ru, G., Simmons, M., Skandamis, P., Suffredini, E., Jacxsens, L., Skjerdal, T., Da Silva Felicio, M. T., Hempen, M., ... Lindqvist, R. (2020). Guidance on date marking and related food information: Part 1 (date marking). *EFSA Journal*, 18(12), e06306.

Li, T., Lloyd, K., Birch, J., Wu, X., Miroso, M., & Liao, X. (2020). A quantitative survey of consumer perceptions of smart food packaging in China. *Food Science & Nutrition*, 8(8), 3977–3988.

Li, T., Messer, K. D., & Kaiser, H. M. (2020). The impact of expiration dates labels on hedonic markets for perishable products. *Food Policy*, 93, 101894.

Lunds Kommun. (2025, March 3). Lund i siffror. Lunds kommun.

Melgaard, C. V., Voss, E., Hansen, M. F., Lassen, M., Hvidtfeldt, M., Pandey, S., Rasmussen, M. A., & Thomsen, M. (2024). Danish consumers' knowledge about and willingness to buy dairy products close to the best-before-date. *Food Frontiers*, 5(2), 494–507.

Mittal, B. (2017). Facing the Shelf: Four Consumer Decision-making Styles. *Journal of International Consumer Marketing*, 29(5), 303–318.

Otles, S., & Sahyar, B. Y. (2016). Intelligent Food Packaging. In *Comprehensive Analytical Chemistry* (Vol. 74, pp. 377–387). Elsevier.

Pandey, S., Bohl, A., Favari, V., Mora, P., Phuyal, S., Sojková, E., Budhathoki, M., & Thomsen, M. (2024). Consumers' willingness to buy meat and seafood products close to the expiry date: An exploratory study from Denmark. *Frontiers in Nutrition*, 11.

Ray, B., DeLong, K. L., Jensen, K., Burns, S., & Luckett, C. (2024). Consumer preferences for foods with varying best if used-by dates: An experimental auction and sensory evaluation analysis. *Food Policy*, 125, 102650.

Region Skåne. (2024). Näringsliv och arbetsmarknad i Lund.

Regulation (EU) No 1169/2011 of the European Parliament and of the Council of 25 October 2011 on the Provision of Food Information to Consumers.

Riesenegger, L., & Hübner, A. (2022). Reducing Food Waste at Retail Stores—An Explorative Study. *Sustainability*, 14(5), Article 5.

Samotyja, U., & Sielicka-Różyńska, M. (2021). How date type, freshness labelling and food category influence consumer rejection. *International Journal of Consumer Studies*, 45(3), 441–455.

Schmidt, J., & Bijmolt, T. H. A. (2020). Accurately measuring willingness to pay for consumer goods: A meta-analysis of the hypothetical bias. *Journal of the Academy of Marketing Science*, 48(3), 499–518.

Schmidt, J., Steiner, M., Krafft, M., Eckel, N., & Dahl, D. W. (2024). Hitting the bullseye: Accurately measuring willingness to pay for innovations with open and closed direct questions. *International Journal of Research in Marketing*, 41(2), 383–402.

Schmidt, K. (2019). Predicting the consumption of expired food by an extended Theory of Planned Behavior. *Food Quality and Preference*, 78, 103746.

- Shao, P., Liu, L., Yu, J., Lin, Y., Gao, H., Chen, H., & Sun, P. (2021). An overview of intelligent freshness indicator packaging for food quality and safety monitoring. *Trends in Food Science & Technology*, 118, 285–296.
- Soltani Firouz, M., Mohi-Alden, K., & Omid, M. (2021). A critical review on intelligent and active packaging in the food industry: Research and development. *Food Research International*, 141, 110113.
- Stankevich, A. (2017). Explaining the Consumer Decision-Making Process: Critical Literature Review. *JOURNAL OF INTERNATIONAL BUSINESS RESEARCH AND MARKETING*, 2(6), 7–14.
- SWECO. (2023). Lund befolkningsprognos 2023-2033.
- Swedish Environmental Protection Agency. (2021).
Good_examples_from_sweden_on_reducing_food_waste.
- Swedish National Food Agency. (2021). Voluntary information—Control wiki.
- Swedish National Food Agency. (2025). Vanliga frågor om datummärkning.
- Taoukis, P., & Tsironi, T. (2016). Smart Packaging for Monitoring and Managing Food and Beverage Shelf Life. In *The Stability and Shelf Life of Food* (pp. 141–168). Elsevier.
- Theotokis, A., Pramataris, K., & Tsiros, M. (2012a). Effects of Expiration Date-Based Pricing on Brand Image Perceptions. *Journal of Retailing*, 88(1), 72–87.
- Theotokis, A., Pramataris, K., & Tsiros, M. (2012b). Effects of Expiration Date-Based Pricing on Brand Image Perceptions. *Journal of Retailing*, 88(1), 72–87.
- Thies, A. J., Altmann, B. A., Countryman, A. M., Smith, C., & Nair, M. N. (2024). Consumer willingness to pay (WTP) for beef based on color and price discounts. *Meat Science*, 217, 109597.
- Tueanrat, Y., Papagiannidis, S., & Alamanos, E. (2021). Going on a journey: A review of the customer journey literature. *Journal of Business Research*, 125, 336–353.
- United Nations Environment Programme. (2024). Food Waste Index Report 2024. Think Eat Save: Tracking Progress to Halve Global Food Waste.
- Wang, J., & Yue, H. (2017). Food safety pre-warning system based on data mining for a sustainable food supply chain. *Food Control*, 73, 223–229.
- Yu, H., Neal, J. A., & Sirsat, S. A. (2018). Consumers' food safety risk perceptions and willingness to pay for fresh-cut produce with lower risk of foodborne illness. *Food Control*, 86, 83–89.
- Zhang, J., Wedel, M., & Bloem, M. W. (2022). Mitigating Food Waste in the Retail Supply Chain: Marketing Solutions. *Journal of Sustainable Marketing*, 3(2), 87–97.

Study the impact of protectants to increase shelf life in dry product

**Andrea
ROJAS**

ECUADOR



andre.rojas150@gmail.com

Profile in a nutshell:

- Master in Food Design and Engineering
- Master in Culinary Innovation
- Master in Nutrition and Food Science
- BSc Food Engineering with Ceneval Award

Interests:

Product development , Research and development, Plant-Based formulations, Yoga, Hiking, Reading, Foodie

Master Thesis hosting lab/company:

Puratos, Andenne, Belgium

Master Thesis tutors:

Stephanie PASSOT, PhD
Cassandre LEVERRIER, PhD

The food industry has shown increasing interest in dry products due to their extended shelf life, improved handling, and consistent fermentation performance. Achieving these benefits requires a comprehensive understanding of the microbial and biochemical dynamics during fermentation. Factors such as acidification, enzymatic activity, moisture levels, and structural changes play a critical role in the success of drying techniques.

This study addresses the following scientific question: How does the use of protectants improve the shelf life of a dry product by increasing the glass transition temperature, while ensuring product stability and industrial applicability? To answer this, the research evaluates the role of protectant formulations in maintaining the viability, rehydration capacity, and overall performance of the dry product (F5).

The objective of this study was to evaluate the impact of different protectant formulations on the viability and storage stability of a dry product, with a focus on the glass transition temperature (Tg). Among the tested formulations, F5 demonstrated the highest protective efficacy.

Moisture sorption behavior was accurately described using the GAB model, which reflected strong water-solid interactions and enabled reliable prediction of equilibrium moisture content for storage optimization. The relationship between Tg, water activity (aw), and water content was investigated to assess the impact of moisture sorption on the physical stability of the F5 formulation compared to the Reference.

As a_w increased, the T_g of the dry product declined, indicating moisture-induced destabilization. However, F5 consistently maintained higher T_g values across all a_w levels, demonstrating enhanced structural stability and reduced sensitivity to water plasticization. Product humidity increased following a type III sorption isotherm, further confirming the moisture sensitivity of the dry product.

As a conclusion, the comparison between the REF and F5 underscores key formulation considerations. While the dry product requires strict a_w control to preserve its glassy state at ambient temperatures, F5 maintains higher T_g values across a broad range of a_w . This provides greater protection against moisture-induced destabilization and supports improved product stability.

CONFIDENTIAL TOPIC

Analysis of public financing of food in Île-de-France

**Marie
SAZERAC**

FRANCE



marie.sazerac@gmail.com

Profile in a nutshell:

- MSc. Food Innovation and Product Design (FIPDes) with specialization in Food Design and Engineering AgroParisTech (France), TU Dublin (Ireland),
- Bachelor in biology from the Sorbonne University and political science from Sciences Po Paris

Interests:

Food innovation, food system, sustainable food

Master Thesis hosting lab/company:

Direction régionale et interdépartementale de l'alimentation, l'agriculture et la forêt, Préfecture Île-de-France

Master Thesis tutors:

Dr Marine MASSON
Hélène PREUX

Context

Internship host: DRIAIF Île-de-France

- Regional and interdepartmental office of the Ministry of Agriculture and Food Sovereignty
- Under the authority of the Regional Prefect
- Contributes to the implementation and monitoring of rural development, land-use planning and sustainable development policies

MISAL (Interagency Food Taskforce)

- Created in 2019 by decree of the Prefect, coordinated by DRIAIF
- Aims to promote interagency cooperation for a systemic approach to food issues





Figure 1. Membership of MISAL

Map 1. Departments of Île-de-France

Background and challenges

- Public funding is key in shaping food systems—but its impact depends on how it is distributed. Keynes (1936) saw public spending as a driver of development; Wagner (1883) saw it as a consequence. Today, public investment is shown to reduce poverty, malnutrition and food insecurity (Tapsoba and Brun, 2023).
- Yet in France, out of €53.6 billion in food-related public funding, less than 10% supports the ecological transition (I4CE, 2024).
- In a context of fragmented food policies, MISAL members fund numerous initiatives across various levels (regional and departmental) and topics (food insecurity, food waste, health).
- The absence of shared tools limits the capacity to identify who funds what, on which themes, and with what potential outcomes.
- A harmonised mapping of actions is thus essential to support evidence-based regional food governance.

Research question

How can we design a harmonised interagency database that enables a strategic, place-based and multi-stakeholder understanding of public funding for food systems in Île-de-France?

Methodology

Phase 1 – Scoping (February)	Phase 2 – Tool Development (March)	Phase 3 – Testing and validation (April)	Phase 4 – Collection (May)	Phase 5: Analysis and deliverables (June)
• Semi-structured interviews with institutional stakeholders (DRIAAF, ARS, etc.) • Co-development of a glossary to clarify and align terms as : ◦ Action: what is the subject of an agreement. ◦ Food (Loi d’avenir pour l’agriculture, l’alimentation et la forêt, 2014): “all actions that ensure that the population has access to safe, healthy, diversified food of good quality and in sufficient quantity” (including urban agriculture, supply chains, etc.).	• Preliminary Excel-based monitoring table • Collaboration with cartography and statistics departments • Data quality principles (atomic cells, dropdown menus, etc.)	• Testing with pilot datasets • Iterative adjustments	• Distribution of a filling-in guide (definitions of SNANC themes, types of action, audiences, etc.). • Support with filling in if necessary.	• Statistical analysis of data concerning the amounts committed or the number of actions (by funder, by theme, by type of action, by target audience, by territory). • Development of the finalized table and a inventory. • Glossary of terms • Excel spreadsheet for data collection • Automatically updated excel results analysis with linked graphs • Template for annual report

Results

- Inventory 2024 : €26.6 million, 448 actions
- Type of action: the most costly initiatives involve food aid (operations and purchases), followed by food chain monitoring systems and educational workshops. The largest number of initiatives involve awareness-raising, nutrition/health workshops and training
- Themes most supported (SNANC guidelines) : social justice (food aid), processing/distribution (food safety and food aid), health and food education.
- Target audiences : actions aimed at people in precarious situations predominate. Young people and the general public are also important targets for prevention initiatives.
- By funder : Differentiated strategies: some services fund few actions with high amounts, others disseminate numerous projects with low amounts.
- Regional distribution: the majority of funding is concentrated in priority social areas.

Discussion

- Two logics coexist: an intensive approach (high funding, targeted actions) and an extensive approach (multiplicity of actions with small amounts). This duality reflects the recommendations of the OECD (2024) for a resilient, place-based system.
- Thematic balance to be strengthened: actions relating to the environment, land use or employment remain marginal in line with the I4CE results (2024).
- Territorial inequalities : creation of departmental ‘food identity maps’ to contextualize the results of the inventory with territorial indicators.

Conclusion and perspectives

- An initial inter-departmental database, providing a cross-sectional view of food policies in the Paris Region.
- Areas for improvement : set up a permanent interdepartmental technical group; add impact and weighting metrics; distinguish in the analysis between incentive and regulatory actions.

Table 1. Example of food identity card

Essonne (91) food identity card			
SNANC themes	Indicators	Departmental data	Ile de France average
Social justice	% population living in priority urban neighbourhoods		
	Poverty rate in %		
	Number of local solidarity contracts		
Health	Human development index		
	Number of local health contracts		
Food education	Number of schools (primary and secondary) involved in structured sustainable food education initiatives (positive food family challenge, etc.) and/or participating in the "milk and fruit at school" programme		
Environment	Percentage of agricultural land used for organic farming and in conversion		
	Concentration of pesticides in groundwater		
	Concentration of pesticides in surface water		
Fight against waste	Number of mass catering establishments that have introduced a system for measuring and/or combating food waste and/or combating food waste and indicating this on "ma cantine"		
Agricultural land	Percentage of land area classified according to land use (agricultural area)		
Mass catering/EGAlim	Number of canteens registered on "ma cantine"		
	Percentage of canteens meeting EGAlim targets		
Production	Average diversity of arable crops		
	Number of farms		
Transformation/Distribution			
Employment	Unemployment rate in %		
Other	Number of Territorial Food Projects (PAT)		
	Number of inhabitants		



References

I4CE. 2024. Le financement public du système alimentaire français : quelle contribution à la transition écologique ?, par Rogissart, L., Lecq, S. et Tayeb,O. Cherif. Paris : I4CE.

Keynes, J. M. 1936. The General Theory of Employment, Interest, and Money. Londres : Palgrave Macmillan.

OCDE. 2024. Politiques agricoles : suivi et évaluation 2024 (version abrégée). Innover pour une croissance durable de la productivité. Paris : OCDE.


Tapsoba, A.F et Brun, M. 2023. Les soutiens publics à l’agriculture et à l’alimentation : entre inégalités et controverses. Prisme. L’analyse de la conjoncture et de l’actualité agricole et agroalimentaire du Crédit Agricole, 41.

Wagner, A. (1883). Three extracts on public finance. In: classics in the theory of public finance. R. A. Musgrave & A. T. Peacock, eds. Macmillan, London

Improvement of the flavour profile of Philadelphia plant-based Cream Cheese and exploration and characterization of alternative vegan protein sources

**Wiktoria
SIENNICA**

POLAND



wiktoria.siennica@gmail.com

Profile in a nutshell:

- M.Sc. Nutrition et Sciences des Aliments (AgroParisTech, FRANCE)
- M.Sc. Culinary Innovation (TU Dublin, IRELAND)
- M.Sc. Scienze e Tecnologie Alimentari (UNINA, ITALY)
- Bac. Management and Production Engineering (Wroclaw, POLAND)

Interests:

Food Innovation, Plant-based dairy alternatives, Travelling, Running

Master Thesis hosting lab/company:

Mondelez International RD&Q Unterhaching, Germany

Master Thesis tutors:

Prof. Raffaele Sacchi (UNINA)

Katerina Milosavljevic, Salvador Donat Luis, Simone Goldbach

Introduction

In recent years, interest in plant-based dairy alternatives has increased due to rising consumer awareness of sustainability and the shift toward dairy-free diets [1],[3],[5]. Despite market growth, formulating plant-based spreads (PBS) remains challenging, particularly when replicating dairy-like properties with clean-label constraints. Fermentation, a traditional process widely applied in dairy, has been introduced to plant-based systems to enhance sensory and functional qualities. This thesis explores the impact of various starter cultures (SC) on improving dairy-associated sensory attributes, such as “creamy” and “buttery” notes, while reducing undesirable cereal flavors from oat-based matrices. Differences in composition and functionality of plant proteins (PP), presence of off-flavors from inherent volatile compounds [2] highlights the challenge and importance in selecting a suitable PP ingredient for PBS application.

Objectives

This research focuses on Plant-Based Spread (PBS), addressing key objectives:

- Develop a “dairy-like flavour” through fermentation by screening and prototyping plant-based spreads with different Starter Cultures (SC) and fermentation temperatures.
- Generate insights into understanding the impact of specific strain presence on fermentation speed, flavour development, as well as viscosity and firmness of the final product.
- Establish a protocol for Plant Protein (PP) evaluation.

Methodology

The Methodology was divided into two parts to meet the set objectives: first part covering SC evaluation and the second, exploring alternative PP for the PBS application. During both stages PBS bench-top production process was implemented (Figure 1) with changes in the ingredient or fermentation temperature depending on the screening stage.

Materials

During SC screening PBS samples were prepared with SC, suitable for plant and vegetable based fermented products. 12 SC were obtained from 4 different suppliers: A,B,C and D. Majority of SC used in the screening belonged to Thermophilic group with two exceptions: C.6 and D.1 being Mesophilic SC. For the second part of the research 8 PP were tested: (P.1-P.8) coming from: different plant sources and varyig in protein concentration.




Figure 1. PBS bench-top production flow chart

Fermentation

Key process step, significant for the characteristics of the final product. Acidification was followed during both screenings: SC and PP. This step allowed to discriminate SC and PP with slower acidification time not allowing to reach target pH of 4,6 within 8 h of the fermentation in order to prevent microbial growth.

Viscosity

The viscosity measurement was conducted using Perten Rapid Visco Analyser 4500- and 4800 (RVA) with the measurement software TCW3. RVA is a cooking, stirring viscosimeter with ramped temperature and shear capability, it provides information on changes of viscosity (cP) of the sample over time (min). The measurement was performed at constant 4°C for 120 min and the rotating speed of the paddle was set at 80 rpm for premix samples and 80 rpm at 10 °C for 120 min for the PBS samples. Viscosity results were compared and then further used for the purpose of choosing the most promising cultures

Cold firmness

Measurement was performed on final formulations from both screenings. The measurement was performed with a TAXT2 Texture Analyser (Stable Micro Systems)(Figure 11) attached with a 45° glass conical test probe. All samples were tempered in a 10 °C fridge 24h before the measurement and the top layer of the sample was scraped off to ensure an even measurement surface with a standardized tool. During measurement the sample was penetrated at a speed of 2.00 mm/s for 10.0 mm with a trigger force of 3.0 g, and the maximum load (in gram) was noted. The measurement was preformed twice on opposite sides of the sample (Figure 2).




Figure 2. Cold Firmness Measurement Principle- Placement

Sensory Evaluation

For the purpose of SC Screening, sensory evaluation with experienced R&D colleagues was conducted on the fermented premix one day after preparation and 7 days after production for PBS samples. All participants completed a scoring sheet, and were asked to compare the samples to the reference using 3-point scale and 5-point (depending on the screening stage) Participants evaluated samples regarding following attributes: overall flavour, sourness, saltiness , cereal/malty flavour, creamy (cream/butter) flavour , sweetness and bitterness.

Results and Discussion

Fermentation

Fermentation was followed. During SC screening two Starter Cultures did not reach desired pH within set time and were excluded from further screening steps: C.6 and D.1 (Figure 3). Highlighting unsuitability of Mesophilic SC for the standard fermentation conditions. Following acidification of samples prepared with alternative PP, allowed to detect key attributes of PP ingredient impacting fermentation time. High concentration of protein was found unfavourable as lower fermentation yield was observed, possibly related to low sugar content, insufficient for the SC to ferment the sample: P.3 and P.4 (Figure 4). Additionally importance of soluble fibre content was highlighted. P.8 during processing formed a viscous mass, creating unfavourable conditions for the SC to ferment the batch.




Figure 3. SC screening- fermentation curve




Figure 4. PP screening- fermentation curve

Viscosity

Viscosity of premixes fermented with following SC was measured (Figure 4). A.2. recorded the highest values, which could be explained by EPS production by the bacteria strain present in this SC. Measurement was conducted on PP Screening premix samples. Obtained results suggest that at the intermediate stage C.1 and C.6 have higher viscosity in comparison with the STD sample(Figure 5).




Figure 4. SC screening viscosity comparison at premix stage




Figure 5. PP screening viscosity comparison at premix stage

Cold firmness

Firmness of the SC trial PBS samples was measured (Figure 6). No significant difference between the Cold Firmness values of the PBSs was recorded indicating that at current processing parameters Firmness of the PBS is not starter culture driven. Differences in viscosity between the premix samples were not transferred to the PBS stage as firmness values were not significantly different. Interestingly high viscosity at premix stage were not transfer to the final product form. As shown on (Figure 7) both alternative PP samples exhibited low firmness values, suggesting possible unsuitability of current processing parameters for the alternative PP matrix.




Figure 6. SC screening- Cold Firmness




Figure 7. PP screening- Cold Firmness (Week 1-Blue, Week 3-Orange)

Sensory Evaluation

Evaluation conducted on Premix samples from the SC assessment allowed to discriminate Starter Cultures not driving the desired attributes and increasing the unwanted flavour profile: C.2+, C.3, C.4 and C.6. Highlighting at the same time SC enhancing desirable “creamy” attributes: C.3+ and A.3 and reducing unfavourable “cereal/malty” notes: A.3 and C.2. (Figure 8). As a result of internal sensory assessment and conducted measurements “most promising” SC were selected and tested at two different temperatures. Finally SC: C.2 at 37°C was selected as providing the best flavour profile to the PBS (Figure 9).




Figure 8. Sensory Assessment of SC Premix Samples




Figure 9. Final Sensory Assessment of PBS samples

PBSs formulated with P.1 and P.6 were evaluated during internal sensory assessment (Figure 10). Overall flavour, sourness and saltiness of the P.6 sample was lower in comparison with the STD sample, on contrary similar values of cereal, malty and bitter attribute were noted. Outstanding sweetness of the sample could be visible in both collected ratings and comments. P.1 sample was characterised with lower creamy attribute, indicating low suitability for PBS application.




Figure 10. Final Sensory Assessment of PBS samples prepared with P.1 and P.6

Conclusion and Recommendation

Conducted measurements and collected sensory evaluation results allowed to distinguish SC: C.2 and A.2, that improved the sample overall profile. C.2 fermented at 37°C was chosen for future up scaling. PP screening highlighted importance of preliminary screening and drew attention to key characteristics of the PP ingredient : protein, sugar and soluble fiber level, and their limiting quantities making the PP ingredient not suitable for the PBS formulation. Over the screening a PP with favorable sensory profile and similar viscoelastic behavior to in comparison to the standard sample was discovered: P.6. However additional research is advised to possibly explore additional processing parameters, more suitable for this PP matrix. Combining both assessments, it would be advised to prepare PBS with P.6 PP and ferment using A.3 SC known for its “sour” notes enhancement which could possibly improve flavor profile of the sample.

CONFIDENTIAL TOPIC

References

- Bryngelsson, David, Stefan Wirsenius, Fredrik Hedenus, and Ulf Sonesson. “How Can the EU Climate Targets Be Met? A Combined Analysis of Technological and Demand-Side Changes in Food and Agriculture.” *Food Policy* 59 (February 2016): 152–64. <https://doi.org/10.1016/j.foodpol.2015.12.012>.
- Fischer, Estelle, Nathalie Cayot, and Rémy Cachon. “Potential of Microorganisms to Decrease the ‘Beany’ Off-Flavor: A Review.” *Journal of Agricultural and Food Chemistry* 70, no. 15 (April 20, 2022): 4493–4508. <https://doi.org/10.1021/acs.jafc.1c07505>.
- Karabekmez Erdem, Tuğba, Hazel Dilşad Tatar, Sermet Ayman, and Yekta Gezginç. “Exopolysaccharides from Lactic Acid Bacteria: A Review on Functions, Biosynthesis and Applications in Food Industry.” *Turkish Journal of Agricul*
- Ningtyas, Dian W., Bhesh Bhandari, and Sangeeta Prakash. “Modulating the Fat Globules of Plant-Based Cream Emulsion: Influence of the Source of Plant Proteins.” *Innovative Food Science & Emerging Technologies* 74 (December 2021): 102852. <https://doi.org/10.1016/j.ifset.2021.102852>.

Tangyu, Muzi, Jeroen Muller, Christoph J. Bolten, and Christoph Wittmann. "Fermentation of Plant-Based Milk Alternatives for Improved Flavour and Nutritional Value." *Applied Microbiology and Biotechnology* 103, no. 23–24 (December 2019): 9263–75. <https://doi.org/10.1007/s00253-019-10175-9>

Vermeulen, S., Campbell, B.M. and Ingram, J., 2012. Climate change and food systems. *Annual Review of Environment and Resources*, 37, pp.195–222, 10.1146/annurev-environ-020411-130608

Experimental study of ice cream freezing

**Aswin
SRIDHAR**

USA



aswinsridhar529@gmail.com

Profile in a nutshell:

- Master of science in food innovation and product design
- Bachelor of technology in biotechnology

Interests:

Gymming, history, learning new things and rock music.

Master Thesis hosting lab/company:

Häagen-Dazs, Arras, France

Master Thesis tutors:

Hayat Benkhelifa, PhD

Xavier Bour

Ice cream, a frozen dessert, can be defined as a food made from a pasteurized mix of dairy products (typically cream and milk), sweeteners and/or sugar, and stabilizers, to which air is incorporated during freezing. This process results in a smooth, creamy texture characterized by a complex matrix of ice crystals, air cells, and a continuous fat phase dispersed within a water-based serum phase.

The freezing unit operation is the principal site of microstructure generation for ice cream. In order to achieve a uniform product quality across various production sites while amplifying desirable product attributes, it is imperative to better understand the effect of process parameters and their interactions with product microstructure.

The scope of this thesis is the data collection and development of capabilities for Häagen-Dazs to set a foundational data set for upcoming projects on the modelling and inline measurement of unit operations like the freezer. The thesis explores the effect of processing conditions on the resultant product quality while simultaneously developing the analysis capabilities to model this unit operation.

CONFIDENTIAL TOPIC

Towards a Circular Future: A Roadmap for Sustainable Industrial Packaging

**Maria Paola
VARGAS CALLEJAS**

BOLIVIA



mariapaolavargascallejas@gmail.com

Profile in a nutshell:

- MSc. Food Innovation and Product Design (FIPDes) with specialization in Food Packaging Design & Logistics, AgroParisTech (France), TU Dublin (Ireland), Lund University (Sweden)
- B.Sc in Production Engineering, Universidad Privada Boliviana (Bolivia)

Interests:

Sustainability, Project Management, Travelling, Cooking.

Master Thesis hosting company:

Alfa Laval AB, Lund, Sweden

Master Thesis tutors:

Henrik PÅLSSON - Lund University

Anna BRÅHAMMAR - Alfa Laval

**Elizabeth
CODJOE**

GHANA



lizabethcodjoe@gmail.com

Profile in a nutshell:

- MSc. Food Innovation and Product Design (FIPDes) with specialization in Food Packaging Design & Logistics, AgroParisTech (France), TU Dublin (Ireland), Lund University (Sweden)
- BSc.in Food Science and Technology, Kwame Nkrumah University of Science and Technology (Ghana)

Interests:

Passionate about creating new food products by utilizing food waste, Innovation and entrepreneurship.

Master Thesis hosting company:

Alfa Laval AB, Lund, Sweden

Master Thesis tutors:

Henrik PÅLSSON - Lund University

Anna BRÅHAMMAR - Alfa Laval

Introduction

The European regulatory landscape is increasingly focused on promoting sustainability and circularity. The Corporate Sustainability Reporting Directive (CSRD) mandates corporate disclosure of environmental and social impacts, enhancing transparency and accountability (Karabeg, 2024). Under ESRS E5, packaging is addressed as part of resource use and circularity, requiring companies to report on their circular economy strategies. Complementing this, the Packaging and Packaging Waste Regulation (PPWR) aims to reduce packaging waste and reinforce circular principles (European Commission, 2025).

Despite these developments, packaging sustainability has historically been undervalued in industrial supply chains—frequently seen as a functional necessity rather than a strategic lever for innovation (Hellström and Olsson, 2017). However, strategic approaches to packaging can offer significant benefits, including material efficiency, optimized logistics, and reduced waste (Pålsson, 2018a).

This thesis investigates Alfa Laval’s current packaging practices across business units, identifying improvement areas and analyzing the impact of evolving sustainability regulations. Using the Packaging Innovation Scorecard (PIS), the study evaluates the company’s packaging innovation capabilities and proposes a roadmap to support its transition toward more sustainable packaging solutions.

Methodology

A qualitative case study methodology was employed to investigate internal practices and barriers (Yin, 2014; Bryman, 2016). The analysis was guided by the Packaging Innovation Scorecard (PIS), a framework that assesses seven subprocesses critical for innovation maturity: Concept Generation, Packaging Development, Process Innovation, Technology Acquisition, Leadership, Systems and Tools, and Resourcing (Pålsson and Hellström, 2023). The primary unit of analysis in this thesis is the packaging management system at Alfa Laval, a global manufacturer of industrial equipment. The study focuses on understanding how packaging is currently managed across different business units, what challenges exist in implementing sustainable packaging practices, and how innovation in packaging can be systematically improved. An overview of the research design is shown in Figure 1.



Figure 1. Research Design

Data collection

To comprehensively assess Alfa Laval’s organizational maturity in packaging innovation, a multi-source qualitative data collection approach was employed. This included semi-structured interviews, on-site observations, and a review of internal documentation. Triangulating these sources enabled a solid understanding of the company’s internal structures, practices, and challenges related to sustainable packaging. Figure 2 summarizes the three primary sources of data and their contributions to the research. A detailed overview of the interviewed stakeholders, their functional roles, and relevance to the Packaging Innovation Scorecard (PIS) subprocesses is presented in Table 1.




Figure 2. Data collection sources

Table 1. Summary of stakeholder areas and their role in packaging management

Stakeholder Area	Role
Sustainability	Provided insights into corporate environmental objectives, current practices, and alignment of packaging decisions with sustainability goals.
Product Development	Offered perspectives on how packaging integrates with product design, especially material selection and design constraints.
Sourcing/ Purchasing	Shared views on supplier selection, cost considerations, and how these align with sustainability efforts.
Packaging Projects	Contributed practical experience regarding implementation, project management, and common challenges in packaging development.
Packaging Supplier	Offered an external viewpoint on technological capabilities, collaboration processes, and alignment with Alfa Laval's goals.

Data analysis

Following data collection, all interviews were transcribed and analyzed alongside internal documents and site visit notes. The qualitative analysis followed the six-phase thematic process described by Byrne (2022) and Adu (2019), including data familiarization, coding, theme identification, and refinement. NVivo software supported coding and pattern recognition. Findings were cross-referenced with the Packaging Innovation Scorecard (PIS) to address the research sub-questions.

Results and Discussion

Packaging decisions at Alfa Laval are shaped by a complex interplay of technical, logistical, organizational, economic, and sustainability-related factors. Rather than being driven by a single dominant concern, decisions often reflect trade-offs among competing priorities.

While product protection and cost-efficiency are consistent baseline concerns, other influencing factors include transport conditions, site-specific constraints, organizational decentralization, and emerging environmental objectives.

The absence of a unified decision-making framework or overarching packaging strategy leads to inconsistent prioritization across sites. For example, one factory may prioritize short lead times due to limited storage capacity, while another emphasizes material sustainability based on regional initiatives.

This variation stems from the company’s decentralized model but highlights the need for strategic alignment. To structure these insights, the study identified five primary categories influencing packaging decisions: technical, logistical, organizational, sustainability, and cost factors.

Scorecard Evaluation

Building on thematic findings, the Packaging Innovation Scorecard (PIS) was used to evaluate Alfa Laval’s innovation maturity across five business units (Figure 3).

The evaluation revealed notable disparities: while some units showed local strengths in areas like Concept Generation and Leadership, others struggled with core processes such as Resourcing and Technology Acquisition.

Three key capability gaps emerged across the organization:

- Lack of dedicated resources for packaging innovation
- Absence of integrated digital tools for packaging data and decision-making
- Minimal formal processes for scouting or adopting new packaging technologies

These gaps echo challenges identified in prior research (Hellström and Olsson, 2017) and emphasize the importance of packaging logistics as a cross-functional concern (Saghir, 2004).

EU Packaging regulation compliance

Alfa Laval is increasingly influenced by evolving EU regulations, including the Packaging and Packaging Waste Regulation (PPWR), the Corporate Sustainability Reporting Directive (CSRD), and Extended Producer Responsibility (EPR). These are shaping company decisions regarding packaging materials, waste management, and data reporting.




Figure 3. Summary of Scorecard Evaluation

In response, various localized sustainability initiatives have emerged. These include waste-reduction efforts such as reusing incoming paper as filling material, standardizing packaging components, and implementing recycled plastic straps. Some sites have introduced lighter cardboard pallets to replace wooden ones, while others aim to phase out plastic entirely. Although the overall approach remains fragmented due to Alfa Laval’s decentralized structure, these initiatives reflect growing commitment within business units to sustainable packaging innovation.

Conclusion

This study reveals that packaging management at Alfa Laval is characterized by decentralization and significant variability across business units and sites. Packaging decisions are driven by a mix of technical, logistical, and organizational factors, with cost concerns often outweighing sustainability objectives. Despite existing frameworks and sourcing strategies, the lack of formal ownership and dedicated roles limits consistent implementation and strategic alignment. Internal barriers, such as fragmented responsibilities, limited packaging expertise, insufficient resources, and weak cross-site coordination, continue to constrain innovation and scalability of sustainable solutions. Through an assessment of packaging innovation maturity, this study proposes a strategic roadmap focused on strengthening governance, competence development, supplier engagement, and data management. This roadmap (Table 2) offers a practical foundation for transitioning Alfa Laval toward a more coordinated, innovation-led, and sustainability-focused packaging strategy—offering broader insights for similar industrial organizations.

Table 2. Summary of Strategic Roadmap

Focus Area	Short Term (0-1 year)	Medium Term (1-3 years)	Long Term (3+ years)
Leadership and Governance	• Appoint Group-level Packaging Coordinator • Update sustainability procedure	• Assign BU-level Coordinators • Communicate packaging targets	• Monitor and review packaging strategies annually
Competence and Resourcing	• Identify skill gaps and training needs	• Launch packaging-focused training programs	• Establish external knowledge partnerships
Supplier Engagement	• Include innovation capability in supplier evaluations	• Implement supplier scorecards and feedback reviews	• Establish long-term collaboration agreements • Replicate solutions across sites
Design Ownership	• Evaluate ownership models (R&D vs supplier-led)	• Standardize handover procedures for supplier-led designs • Build in-house capabilities if needed	• Align design responsibilities with product development and site capabilities
Innovation and Scaling	• Document pilot initiativesDevelop tracking formats	• Launch Packaging Innovation Library • Host quarterly innovation forums	• Establish routines for scaling innovationsIntegrate continuous improvement
Data and Reporting	• Define packaging data structure and responsibilities	• Enhance data quality across ERP systems • Increase supplier data requirements	• Integrate packaging data into central reporting and decision-making

References

- Adu, P. (2019) A step-by-step guide to qualitative data coding. Routledge. Available at: <https://www.taylorfrancis.com/books/mono/10.4324/9781351044516> (Accessed: 4 April 2025).
- Alfa Laval (2024) Organization for close customer relations. Available at: <https://www.alfalaval.com/about-us/our-company/organization/> (Accessed: 17 February 2025).
- Bryman, A. (2016) Social Research Methods. Oxford University Press.
- Byrne, D. (2022). Project management in qualitative research. Los Angeles: SAGE Publications.
- Garcia-Arca, J., Comesaña-Benavides, J.A., Gonzalez-Portela Garrido, A.T. and Prado-Prado, J.C. (2021) 'Methodology for selecting packaging alternatives: an "action research" application in the industrial sector', Central European Journal of Operations Research, 29(4), pp. 1427–1446. <https://doi.org/10.1007/s10100-020-00724-3>
- Han, J. (2017) 'Exploitation of architectural knowledge and innovation', Journal of Open Innovation: Technology, Market, and Complexity, 3(3), pp. 1–15. <https://doi.org/10.1186/s40852-017-0068-x>
- Hellström, D. and Olsson, A. (2017) 'Managing Packaging Design for Sustainable Development: A Compass for Strategic Directions', Wiley-Blackwell [Preprint].
- Olsmats, C. and Dominic, C. (2003) 'Packaging scorecard – a packaging performance evaluation method', Packaging Technology and Science, 16(1), pp. 9–14. <https://doi.org/10.1002/pts.604>
- Pålsson, H. and Hellström, D. (2023) 'Packaging innovation scorecard', Packaging Technology and Science, 36(11), pp. 969–981. <https://doi.org/10.1002/pts.2769>
- Pålsson, H. (2018a). Packaging logistics – Understanding and managing the economic and environmental impacts of packaging in supply chains. Lund: Lund University, Division of Packaging Logistics.
- Quintão, C., Andrade, P. and Almeida, F. (2020) 'How to improve the Validity and Reliability of a Case Study', Journal of Interdisciplinary Studies in Education, 9(2).
- Saghir, M. (2004) 'THE CONCEPT OF PACKAGING LOGISTICS'.
- Yin, R.K. (2014) 'Case Study Research Design and Methods', Canadian Journal of Program Evaluation, 30(1).

Valorization of Agricultural By-products: Nanocellulose Barrier Films for Sustainable Food Packaging

**Sreshtha
VERMA**

INDIA



sreshtha.2018fth065@ihe.du.ac.in

Profile in a nutshell:

- MSc. in Food Innovation and Product Design (FIPDes) with specialisation in Packaging Design & Logistics, Lund University (Sweden), AgroParisTech (France), TU Dublin (Ireland).
- BSc.(Honors) in Food Technology, University of Delhi.

Interests:

New Product Development, Bio-based Packaging.

Master Thesis hosting lab/company:

Laboratoire de Génie des Procédés et Matériaux
(CentraleSupélec, France)

UMR SayFood (INRAE, AgroParisTech, France)

Master Thesis tutors:

Chloé Chevigny & Giana Perré (AgroParisTech)

Joel Casalinho & Patrick Perré (CentraleSupélec)

Lars Palm (Lund University)

Introduction

The persistent reliance on petroleum-based polymers for food packaging has contributed significantly to environmental challenges. This thesis investigated the valorization of lignocellulosic agricultural by-products, such as corn-cob, artichoke, coffee husks, and grape pomace, as sources for high-performance nanomaterials. The study focused on fabricating multilayer films composed of polylactide (PLA), chitosan tie-layer, and nanocellulose extracted from agro-industrial residues to develop sustainable alternatives to conventional plastic barriers.

Methodology & Objectives

The study systematically evaluated bio-based multilayer films by optimizing preparation protocols for stable cellulose nanofiber (CNF) and cellulose nanocrystal (CNC) suspensions from agricultural waste streams, then characterizing their barrier properties and transport mechanisms.

Films were constructed using a three-layer architecture: corona-treated PLA film as the hydrophobic core, chitosan as a biodegradable tie-layer forming electrostatic bonds between PLA and nanocellulose, and multiple nanocellulose layers deposited via bar-coating.

Barrier performance was evaluated using:

- *Dynamic Vapor Sorption (DVS)*: Measured water vapor uptake and diffusion coefficients
- *Long-term Back-Face Measurement*: Monitored water vapor and oxygen transport over extended periods under controlled environmental conditions to quantify oxygen barrier performance under dynamic humidity and elucidate molecular transport mechanisms.

CONFIDENTIAL TOPIC

Optimization and validation of a pilot-scale protocol for assessing the technological suitability of wheat flours in croissant production

**Kawtar
ZAAZAI**

MOROCCO



Kawtarzaazai@gmail.com

Profile in a nutshell:

- Master of Science in Food Innovation and Product Design
- Bachelor of Food engineering

Interests:

Innovative products, plant-based products, travel, and music

Master Thesis hosting lab/company:

Mondelez international

Master Thesis tutors:

Silvia Tagliamonte


Anne-sophie Contamine

The laminated bakery category, especially croissants, presents unique technical challenges that require highly functional wheat flours. Conventional analytical tools, such as the farinograph, alveograph, and extensograph, are commonly used for flour assessment but fall short in predicting flour performance under the complex, large-strain conditions of croissant production. Inconsistent product outcomes, high production costs, and the increasing variability in flour properties, underlines the need for application-specific evaluation tools.

The aim of this study was to develop and optimize a standardized, pilot-scale protocol to assess the technological performance of wheat flours in croissant production. The protocol was designed to closely replicate industrial processing steps, including mixing, lamination, fermentation, and baking, and to integrate structural and rheological measurements relevant to flour functionality. Two industrial types of wheat flours, were tested over multiple production days to evaluate both repeatability and robustness.

This research fills a critical gap in both academic and industrial settings by providing a product-specific protocol framework that links flour rheology and end-product quality under realistic production conditions. The methodology can offer R&D and quality assurance teams a valuable tool to screen flours for croissant applications, reduce dependency on trial-and-error, and contributes to establishing more predictive and standardized flour assessment practices within the bakery industry.

CONFIDENTIAL TOPIC



Future World Product
Mix Food Naples Dublin Young Design
Talents Knowledge Culture Discovery Languages
Fipdes Paris New Friends Innovation

www.tanadesign.eu

www.fipdes.eu

Contact

fipdes@agroparistech.fr